

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

NM-068043

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Harris Fed.

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR B.L. AND SURVEY OR AREA

Sec. 27, T-15-S, R-27-E
N.M.P.M.

12. COUNTY OR PARISH

Chaves

13. STATE

New Mexico

1. OIL WELL ☐ GAS WELL ☒ OTHER Wildcat

2. NAME OF OPERATOR

Read & Stevens, Inc.

3. ADDRESS OF OPERATOR

P. O. Box 2126, Roswell, New Mexico 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)
At surface

1980' FEL & 660' FSL Sec. 27, T-15-S, R-27-E, N.M.P.M.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3472.2' GR - 3484' RKB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spudding & Surface Casing

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded well @ 5:15 P.M., 3-24-75. Drilled 17 1/2" hole to 350'. Ran 10 joints 13 3/8", 48#, H-40, S.T. & C. casing, total of 350', set at 349' RKB. Cemented w/100 sx. Halliburton lightweight cement w/1% gel, 5# gilsonite & 1/4# floreal per sx., followed by 350 sx. Class "C" cement w/1/4# floreal & 2% CaCl₂ per sx. Cement did not circulate. Filled backside to top of casing w/5 yards readymix cement. Plug down @ 5:30 P.M., 3-25-75. WOC for 12 hours. Pressure tested casing to 1000# for 30 min., held OK.

RECEIVED

APR 9 1975

D. C. C.
ARTESIA, OFFICE

RECEIVED

MAR 28 1975

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Agent

DATE

3-26-75

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side