

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on Items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 33.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.

Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES: SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES				38. GEOLOGIC MARKERS	
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	MEAS. DEPTH THRU VENT. DEPTH
Atoka	9000	9200	DST#1 ISIP 286 1'; IFP 157-157-20"; FF 157 2'; FSIP 389 4'; Hyd 4696, Temp 140°, Rec'd 10' DM, sp1 ch 700cc DM	Yates Queen Grayburg San Andres Tubb Abo Wolfcamp Penn Canyon Strawn Atoka Morrow Miss Lm	708 1467 1816 2104 4906 5698 6945 7758 8340 8910 9137 9307 9460
Morrow	9200	9490	DST#2 Pkr failed, IHP 4786, Temp 138°		
Morrow	9260	9490	DST#3 TO w/gd blo, inc. to strong blo. GTS 15", 1' ISI TO w/strong blo. Est. 450 MCF, 15" dec. to 315 MCF, 55" dec. to 310 MCF, inc. to 350 MCF for last hr. IHP 4781 1' ISIP 3403, 15" IFP 289, 5' FFP 289-325, 6' FSIP 4036, FHP 4681. Temp 160°, Rec 540' HGC DM. Sp1. ch. 0#, .8 CFG 320cc DM.		