

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TR  
(Other Instructi  
verse side)CATE\*  
OR RE-Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0284972-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal "DH"

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

South Lucky Lake  
Unit Queen P.525211. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 27-15S-29E

Unit D NMPM

12. COUNTY OR PARISH

Eddy Charles

13. STATE

NM

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL  
WELL ☒ GAS  
WELL ☐ OTHER

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th Street - Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

330' FNL &amp; 330' FWL of Section 27-15S-29E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3835' GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Set Prod. csg, perf, treat X

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any  
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-  
nent to this work.)\*TD 1818'; PBTD 1804'. Ran 45 joints of 5½" 15.5#, J-55 (1803') of casing  
set at 1804'. 6 centralizers at 1764, 1724, 1684, 1404, 1364, 1320 & 1  
Guide shoe. Cemented w/150 sacks of Class "C" cement. PD 5:30 PM 7-30-76.Perforated 1760-1770' (10') w/40 shots (4 SPF) .42" holes. Treated w/  
20000 gallons lease crude and 1500 gallons of 15% acid. 25000# 20-40  
sand and 2500# of 10-20 sand.

RECEIVED

AUG 17 1976

D. C. C.

ARTESIA, OFFICE

RECEIVED

AUG 13 1976

U. S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

*Christine Johnson*

TITLE

Geol. Secty

DATE

8-12-76

(This space for Federal or State office use)

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED BY  
AUG 13 1976  
M. L. BEEKHUIS  
ACTING DISTRICT ENGINEER

\*See Instructions on Reverse Side