

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OCT 17 '94

WELL API NO.

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

L-96

7. Lease Name or Unit Agreement Name

Bogle State

8. Well No.

1

9. Pool name or Wildcat

Buffalo Valley Penn Und

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL  
WELL ☐

GAS  
WELL ☒

OTHER ☐

2. Name of Operator

Louis Dreyfus Natural Gas Corporation

3. Address of Operator

14000 Quail Springs Pkwy, Ste. 600, Okla. City, OK 73134

4. Well Location

Unit Letter J : 1650 Feet From The East Line and 1650 Feet From The South Line

Section

8

Township

15S

Range

28E

NMPM

Chaves

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3535 Gr.

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. MIRU Workover Unit.

2. Release packer @ 8777', TOOH & lay down tubing.

3. Set 4-1/2" OD CIBP @ 8760'. Dump bail 35' of cement on plug.

4. Cut of casing and pump 100 ft. cement plug at cut off point. + Tag

5. TOOH & lay down casing. 6. 100' cement plug @ 6500'. 7. 100' cement plug @ 4500'.

9. Spot 100 ft. cement plug @ 380 ft. surface casing shoe. 8. 100' cement plug @ 2200'.

10. Spot 75 ft. plug within 3 ft. of surface.

11. Cap well w/ ID plate and mark stub location w/ 4" marker 4' above ground level.

12. Restore location.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE

Engineering Tech.

DATE 10/4/94

TYPE OR PRINT NAME

Carla M. Lisle

TELEPHONE NO. 405/

749-5255

(This space for State Use)

SUPERVISOR, DISTRICT II

APPROVED BY

TITLE

DATE

OCT 24 1994

CONDITIONS OF APPROVAL IF ANY: