

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

16798

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR
MARALO, INC.

3. ADDRESS OF OPERATOR
P. O. Box 832, Midland, Texas 79702

4. LOCATION OF WELL (Report location clearly and in accordance with State requirements. See also space 17 below.)
At surface

1980' FSL & 1980' FEL Section 12

MAR 9 1977

14. PERMIT NO. 15. ELEVATIONS (Show whether D.T. or E.T.)
3695.1 GR

7. UNIT AGREEMENT NAME
Butler Springs Unit

8. FARM OR LEASE NAME
Butler Springs Unit

9. WELL NO.
3

10. FIELD AND POOL, OR WILDCAT
Wildcat Queen

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 12, T-15-S, R-28-E

12. COUNTY OR PARISH 13. STATE
Chaves New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF <input type="checkbox"/>	PULL OR ALTER CASING <input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	MULTIPLE COMPLETE <input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	ABANDON* <input checked="" type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
(Other) <input type="checkbox"/>	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF <input type="checkbox"/>	REPAIRING WELL <input type="checkbox"/>
FRACTURE TREATMENT <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
SHOOTING OR ACIDIZING <input type="checkbox"/>	ABANDONMENT* <input type="checkbox"/>
(Other) <input type="checkbox"/>	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Propose to spot 100' cement plug at total depth (2179'); 100' cement plug immediately below base of salt; 100' cement plug over 8-5/8" OD casing shoe (350'); 30' cement plug at surface with appropriate dry hole marker.

Well fluid between cement plugs to be fresh water with 25# gel per barrel.

Cement plugs to be spotted by displacement thru tubing.

RECEIVED

MAR 02 1977

**U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO**

18. I hereby certify that the foregoing is true and correct

SIGNED *Guillermo L. Lujan*

TITLE Production Clerk

DATE 2-24-77

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

APPROVED
[Signature]
ACTING DISTRICT ENGINEER