

NO. OF COPIES RECEIVED	
DISTRIBUTION	
AMT A FE	
ILE	
U.S.G.S.	
AND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

APR 5 1977

O.C.C.

ARTESIA OFFICE

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. K-6844
7. Unit Agreement Name
8. Farm or Lease Name Lula
9. Well No. 2
10. Field and Pool, or Valued Buffalo Valley <i>Pool</i>
12. County Chaves

SUNDRY NOTICES AND REPORTS ON WELLS
DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REOPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT TO DRILL C-101 FOR SUCH PROPOSALS.

OIL WELL ☐ GAS WELL ☒ OTHER ☐

Name of Operator
Holly Energy, Inc.

Address of Operator
P. O. Box 726, Artesia, New Mexico 88210

Location of Well
UNIT LETTER D 990 FEET FROM THE North LINE AND 990 FEET FROM
THE West LINE, SECTION 7 TOWNSHIP 15-S RANGE 28-E NMPM.

11. Elevation (Show whether DF, RT, CR, etc.)
3690.7 GL

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
WELL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded well at 12:30 AM on March 22, 1977. On March 22, 1977 ran 8 joints of 13 3/8" 48# H-40 casing and set at 362'. Cemented with 525 sacks of Class C cement.

On March 25, 1977 ran 41 joints of 8 5/8" 28# casing and set at 1656'. Cemented with 600 sacks of Halliburton Light and 200 sacks of Class C 2% CaCl cement. Cement didn't circulate. Ran a Temperature Survey and found 600' from surface. One inched in 4 stages with 100 sacks of cement in each stage and brought cement to surface.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

BY Robert Loyd TITLE Superintendent DATE March 29, 1977

APPROVED BY _____ TITLE _____ DATE _____
ADDITIONS OF APPROVAL, IF ANY: