

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE  
(Other instructions  
reverse side)Copy to SF  
Form approved  
Budget Bureau No. 42-R1424.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> Dry		5. LEASE DESIGNATION AND SERIAL NO. NM 17571	
2. NAME OF OPERATOR Yates Petroleum Corporation		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR 207 South 4th Street - Artesia, NM 88210		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 660" FSL & 1980' FEL of Sec. 33-15S-26E		8. FARM OR LEASE NAME Riverbend "HR" Federal	
14. PERMIT NO.		9. WELL NO. 1	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3422' GR		10. FIELD AND POOL, OR WILDCAT Wildcat	
OCT 25 1977 RECEIVED U.S. GEOLOGICAL SURVEY ARTESIA, NEW MEXICO		11. SEC., T., R., M., OR BLE. AND SURVEY OR AREA Sec. 33-15S-26E Unit 0 NMPM	
OCT 27 1977		12. COUNTY OR PARISH Chaves	
		13. STATE NM	

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐  
☐  
☐  
☐

PULL OR ALTER CASING

☐  
☐  
☒  
☐

FRACTURE TREAT

MULTIPLE COMPLETION

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

## ARTESIA, OFFICE

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐  
☐  
☐  
☐

REPAIRING WELL

☐  
☐  
☐  
☐

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

This well tested Non-commercial and we propose to P & A the well. Verbal approval was received from Mr. Leon Beckman, Assistant District Engineer, U. S. Geological Survey in Artesia on October 18, 1977 to plug the well as follows (also see enclosed exhibit):

1. Pull packer and any sucker rods in the well
2. Run tubing and fill bottom of hole and perforated zone with cement (5350- to 5582').
3. Shoot off 4½" casing at 4550' and pull.
4. Fill hole with mud and pour a 300' cement plug from (4300-4600') in order to segregate top of Abo zone from other zones and seal off the cut-off portion of 4½" casing.
5. Apply a 100' cement plug at 2200-2300' to seal off the top of the Glorietta formation (2253').
6. Pour a plug at base of 8-5/8" casing (1390') from 1350' to 1450'.
7. Set a 25' cement plug at the surface and set dry hole marker.
8. A mud laden fluid consisting of 25# gel/bbl water will be set between all plugs.
9. Clean up location, level and restore surface.

18. I hereby certify that the foregoing is true and correct

SIGNED

Budd Hebert

TITLE

Land Engineer

DATE

10-21-77

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OR APPROVAL, IF ANY:

TITLE

DATE

\*See Instructions on Reverse Side

# RIVERBEND HR FEDERAL #1 GGO TSL # 198 FEL SEC 33 TISS R2GE

PROPOSED

EXISTING

