

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Amoco Prod. Co.</u>		Lease <u>State ET</u>		Well # <u>1</u>	
Location of Well	Unit ^c <u>990 N 1650W</u>	Section <u>36</u>	Township <u>15</u>	Range <u>27</u>	County <u>Chavez</u>
Drilling Contractor <u>Landis Dily Co.</u>			Type of Equipment <u>Rotary to start 11-21-77</u>		

APPROVED CASING PROGRAM

* witness

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>17 1/2</u>	<u>11 3/4</u>	<u>42</u>		<u>850</u>	<u>cin.</u>
* <u>11</u>	<u>8 5/8</u>	<u>24</u>		<u>1800</u>	<u>"</u>
<u>7 7/8</u>	<u>5 1/2</u>	<u>14-15.5</u>		<u>9100</u>	<u>"</u>

Casing Data:

Int. 46 joints of 8 5/8 inch 32 # Grade J-55

✓ (Approved) (Rejected)

Inspected by Mike Stubblefield date 12/20/77

Cementing Program

Size of hole 12 1/4 Size of Casing 8 5/8 Sacks cement required 1600

Type of Shoe used Guide Float collar used Insert Btm 3 jts welded Yes

TD of hole 1796 Set 1806 Feet of 8 5/8 Inch 32 # Grade J-55

New used csg. @ 1796 with 200 sacks neat cement around shoe

+ 1400 sax Halliburton additives # 5 Gilsinite - 1/4 # Flo Seal - # 8 Salt

Plug down @ 4:30 (AM) (PM) Date 12/21/77

Cement circulated Yes No. of Sacks 200

Cemented by Halliburton Witnessed by MW/M.S.

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: Last Break c 1620'

Cement 1-8' above shoe - 11 Ft above float, no baskets used.