

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPI
(Other instructions
verse side)FE-
re-Form approved
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <u>Dry Hole</u>		5. LEASE DESIGNATION AND SERIAL NO. <u>NM-7301</u>	
2. NAME OF OPERATOR <u>Harvey E. Yates Company</u> ✓		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR <u>P. O. Box 1933, Roswell, New Mexico 88201</u>		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) <u>At surface</u> <u>660' FNL & 1980' FWL</u>		8. FARM OR LEASE NAME <u>East Lake Arthur Federal</u>	
14. PERMIT NO.		9. WELL NO. <u>2</u>	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) <u>3442.6' GL</u>		10. FIELD AND POOL, OR WILDCAT <u>Wildcat</u>	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA <u>Sec. 29, T-15S, R-27E</u>	
		12. COUNTY OR PARISH <u>Chaves</u>	
		13. STATE <u>N. M.</u>	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

We propose to plug and abandon as follows and work will start June 10, 1978:

1. CIBP at 2280' KB with 35' cement on top.
2. SV-EZ squeeze retainer at 1970' KB. Squeeze perfs 2074'-2116' with 150 Sx.
3. CIBP with 35' cement on top at 1880' KB.
4. CIBP with 35' cement on top at 1040' KB.
5. Baker squeeze retainer at 722' KB. Squeeze perfs at 770' with 25 Sx.
6. 25 Sx plug from 630' to 530'.
7. 10 Sx plug from 60' to surface.
8. Install dry hole marker on top and clean up location.

RECEIVED
JUN 29 1978
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Engineer

DATE

June 28, 1978

(This space for Federal or State office use)

APPROVED BY

TITLE

ACTING DISTRICT ENGINEER

DATE

AUG 4 - 1978

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side