

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1 ✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

RECEIVED

NOV 27 1978

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.
L-1511

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input checked="" type="checkbox"/> Dry hole	7. Unit Agreement Name
2. Name of Operator McClellan Oil Corporation ✓	8. Farm or Lease Name M & M State
3. Address of Operator P.O. Box 848, Roswell, New Mexico 88201	9. Well No. 1
4. Location of Well UNIT LETTER L 1980 FEET FROM THE South LINE AND 990 FEET FROM THE West LINE, SECTION 32 TOWNSHIP 15-S RANGE 29-E NMPM.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 3747' G.L.	12. County Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

On November 17, 1978, this test was plugged and abandoned as follows :
Bailed hole dry. Pumped 35 sx cement to total depth (2365'); 35 sx 1550-1650 (Queen sand); 35 sx 275-375 (8 5/8" csg. at 320'); 20 sx plug at surface. Heavy mud pumped between all plugs. Will set dry hole marker and restore surface as near as possible to it's original condition.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Paul J. McClellan TITLE Operator DATE 11/24/78

APPROVED BY Mike Stollfeld TITLE OIL AND GAS INSPECTOR DATE JUL 12 1979

CONDITIONS OF APPROVAL, IF ANY: