

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 140
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Mess Petr. Co.</i>		Lease <i>White State</i>		Well # <i>1</i>	
Location of Well	Unit <i>6603 1880e</i>	Section <i>35</i>	Township <i>15</i>	Range <i>27</i>	County <i>S. Chaves</i>
Drilling Contractor <i>merano</i>			Type of Equipment <i>Rotary to start approx. 5-20-80</i>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>17 1/2"</i>	<i>13 3/8"</i>	<i>48</i>		<i>350</i>	<i>400 cu.</i>
<i>11 "</i>	<i>8 5/8"</i>	<i>24</i>		<i>1900</i>	<i>1100 "</i>
<i>7 7/8"</i>	<i>4 1/2"</i>	<i>10.5 & 11.6</i>		<i>9400</i>	<i>900</i>

Casing Data:

Surface _____ joints of _____ inch _____ # Grade _____
(Approved) (Rejected) _____

Inspected by _____ date _____

Cementing Program

Size of hole *11"* Size of Casing *8 5/8* Sacks cement required _____

Type of Shoe used *guide* Float collar used *inset* Btm 3 jts welded *yes*

TD of hole *1850'* Set *1880'* Feet of *8 5/8* Inch *24* # Grade *K-55*

New-used csg. @ *1880'* with *20029* sacks neat cement around shoe
+ *825* sax *Pacemaker* light additives *5# gibsonite, 6# zeph*

Plug down @ *4300* (AM) (PM) Date *3/21/80*

Cement circulated *yes* No. of Sacks *125*

Cemented by *Western cementing* Witnessed by *Mike Stubbfield*

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: _____

centralizers w 1875-1825-1745' *Full returns*
Last dry break @ 1314'