

MINERAL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

5a. Indicate Type of Lease	
State ☒	Free ☐
5. State Oil & Gas Lease No.	
LG 5608	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)

RECEIVED

AUG 6 1980

1. OIL ☐ WELL ☐ GAS ☒ WELL ☐ OTHER ☐	7. Unit Agreement Name
2. Name of Operator DEPCO, Inc. ✓	8. Farm or Lease Name Mesa St. Com.
3. Address of Operator 800 Central, Odessa, Texas 79761	9. Well No. 1
4. Location of Well UNIT LETTER J 1980 FEET FROM THE East LINE AND 1980 FEET FROM THE South LINE, SECTION 31 TOWNSHIP 15S RANGE 28E NMPM.	10. Field and Pool, or Wildcat Wildcat Miss
15. Elevation (Show whether DF, RT, GR, etc.) 3575.7 GR.	12. County Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☒	OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7-24-80 Drld. 7 7/8" hole from 1950'-9410'.
7-25-80 Ran logs.
7-26-80 Vann Tool Co. set BP. @ 1440'. Perf. 3 holes @ 1088'. Pumped 500 sx. Class "H" cmt. w/16# salt per sx. 2000 gals. flo-check. Followed w/500 sx. Class "H", w/16# salt per sx. 2000 gals. flo-check, 400 sx. Class "C" w/4% ca. cl. & 53 bbls. fresh wtr. SD. press. 1000# then dropped off to 700#. Plug down @ 5:00 AM. WOC.
7-27-80 Ran temperature survey after 10 hrs. Top of cmt. 300'. Tagged cmt. @ 834'.
7-28-80 Ran bit. Drld. out cmt. soft cmt. 834'. firm cmt. 975' down to 1088'. Circ. hole w/fresh water pulled bit out of hole. Ran cmt. bond log showed 100% cmt. from surface to 300'. Showed free pipe from 300'-1060'. 4' section from 1060-1064' w/100% bond. Showed two stringers 1064'-1430'. Vann Tool Co. perf. 3 more shots @ 900'. Ran RTTS pkr. on drld. pipe set @ 800'. Pumped 400 sx. Class "C" w/4% ca. cl. pumped in @ 100%. SIP 800#.
7-29-80 Press. up 1000# perf. held alright. Ran cmt. bond log. Drld. out BP & pushed to bottom.
7-30-80 Circ. 4 hrs layed down drld. pipe. Ran 29 jts. N-80 4 1/2" 11.6# csg. 1165.06', guide shoe & automatic float collar. Ran 163 jts. J-55 4 1/2" 11.6# 6575.95', 42 jts. N-80 4 1/2" 11.6# 1670.27' set @ 9409.27'. Cmt. w/350 sx. Halliburton lite 5# KCL, 3/10 of 1% CFR=2, w/460 sx. Class H, 5# KCL 3/10 of 1% CFR-2. Plug down @ 3:00 AM. Drop bomb to open DV tool back to surface 4 hrs. Pumped 400 sx. Class C, 4% ca. cl. Circ. 75 sx. Plug down @ 7:30 AM. Released rig @ 12:00 AM. 7-30-80.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED R. L. Denney R. L. Denney TITLE Production Clerk DATE 8-5-80

APPROVED BY W. A. Gussert TITLE SUPERVISOR, DISTRICT II DATE AUG 14 1980

CONDITIONS OF APPROVAL, IF ANY: