

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-0115465A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Toles Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 34-15S-27E

12. COUNTY OR PARISH

Chaves

13. STATE

N.M.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL ☐ WELL GAS ☒ WELL OTHER

2. NAME OF OPERATOR

Read &amp; Stevens, Inc. ✓

3. ADDRESS OF OPERATOR

P. O. Box 1518, Roswell, New Mexico 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

660' FSL &amp; 1980' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3518.2 GR

16.

## Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

Casing &amp; cement job

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any  
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-  
nent to this work.)\*

Well spudded 7:00 P.M., 9-16-80. On 9-17-80, reached TD 383'. Ran 10 jts., total of 371', 13 3/8", 48#, H-40, S. T. & C. casing, set @ 383'. Cemented w/350 sx. Halco Lite cement w/5# gulsonite per sx. & 1/4# flocele per sx. Followed w/200 sx. Class "C" cement w/2% CaCl<sub>2</sub> & 1/4# flocele per sx. Plug down 10:45 A.M., 9-17-80. Cement circulated.

Drilled an 11" hole to TD 1730' @ 11:00 A.M., 9-19-80. Ran 43 jts., total of 1718', 8 5/8", 24#, J-55, S. T. & C. casing, set @ 1730'. Cemented w/100 sx. Halco Lite cement w/8# gulsonite & 1/4# flocele per sx. Followed w/200 sx. Class "H" cement w/2% CaCl<sub>2</sub>. Plug down 5:20 P.M., 9-19-80.

RECEIVED

ACCEPTED FOR RECORD

OCT 2 1980

U.S. GEOLOGICAL SURVEY

ROSWELL, NEW MEXICO

RECEIVED

OCT 1 1980

U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

OCT 8 1980

O. C. D.  
ARTESIA, OFFICE

18. I hereby certify that the foregoing is true and correct

SIGNED

Shari Hamilton

TITLE Authorized Agent

DATE 9-30-80

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side