

N.M.O.G.D. 001-

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a well. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. NM-068043	
2. NAME OF OPERATOR READ & STEVENS, INC.		6. IF INDIAN, ALLOTTEE OR TRIBE NAME -	
3. ADDRESS OF OPERATOR P.O. BOX 1518, ROSWELL, NM 88201		7. UNIT AGREEMENT NAME -	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 990' FWL & 1650' FNL		8. FARM OR LEASE NAME HARRIS FEDERAL COM	
14. PERMIT NO. -		9. WELL NO. 5	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3567.0' GR		10. FIELD AND POOL, OR WILDCAT BUFFALO VALLEY PENN	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA SEC. 25-15S-27E	
		12. COUNTY OR PARISH CHAVES	
		13. STATE NM	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐CASING & CEMENT JOB ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.* If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

2-25-81: DRILLED TO 1705', RAN 23 JTS., TOTAL 1693', 8 5/8", 24#/FT. ST&C, SET AT 1705'. CMT WITH 250 SX. HALLIBURTON LIGHT W/5# GILSONITE, 1/4# FLOCELE, FOLLOWED BY 300 SX. CLASS "C" 2% CACL₂. PLUG DOWN 2-26-81 @ 7:45 A.M. WOC 18 HRS. TST CSG AT 1000 PSI FOR 30 MIN., TESTED OKAY. TOC 90 FT. FROM SURFACE.

RECEIVED
MAR 2 1981
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

B. Stobbs

TITLE DRLG. & PROD. MGR.

DATE 2/26/81

(This space for Federal Agency use)

APPROVED FOR RECORD
PETER W. CHESTERAPPROVED BY
CONDITIONS OF APPROVAL IF ANY

MAR 2 1981

TITLE

DATE

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side