

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

5a. Indicate Type of Lease
State ☐ For ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT DEPTH. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

AUG 24 1981

Name of Operator
Yates Petroleum Corporation
Address of Operator
207 South 4th St., Artesia, NM 88210

O. C. D.
ARTESIA, OFFICE

7. Unit Agreement Name

8. Farm or Lease Name
Carroll Jackson "RO"

9. Well No.
1

Location of Well
UNIT LETTER F, 1980 FEET FROM THE North LINE AND 1980 FEET FROM THE West LINE, SECTION 28 TOWNSHIP 15S RANGE 25E N.M.P.M.

10. Field and Pool, or Wildcat
Wildcat

15. Elevation (Show whether DF, RT, GR, etc.)
3472' GR

12. County
Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

FORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PLUG OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPERATIONS ☐
CASING TEST AND CEMENT JOB ☒
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐
OTHER ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 12-1/4" hole at 4:15 PM 8-10-81. TD 1030'. Ran 26 jts of 8-5/8" 24# J-55 ST&C casing set at 1030'. 1-Notched Guide shoe set at 1030'. 1-Flapper insert float set at 990'. Cemented w/200 sacks Thixolite, 2#/sack Permacheck, 1/2#/sack celloseal, 10#/sack Gilsonite, 2% CaCl, 550 sacks 65/35 Poz, 2#/sack Permacheck, 1/2#/sack celloseal & 3% CaCl. Tailed in w/150 sacks Class "C" 3% CaCl. Compressive strength 1250 psi. PD 7:30 PM 8-12-81. Bumped plug to 750 psi, released pressure & float held okay. Cement did not circulate. WOC 6 hours. Ran Temperature Survey & found top of cement at 390'. Ran 1". Tagged cement at 363'. Spotted 50 sacks Thixolite, 2# Permacheck, 1/2# celloseal & 3% CaCl. PD 2:15 AM 8-13-81. WOC 1 hour and 20 minutes. Ran 1". Tagged cement at 80'. Spotted 100 sacks Class "C" Neat. PD 4:00 AM 8-13-81. WOC 1-1/2 hours. Ran 1". Tagged cement at 75'. Spotted 50 sacks Thixolite, 2# Permacheck, 1/2# celloseal & 3% CaCl. PD 5:50 AM 8-13-81. WOC 1 hour. Ran 1". Tagged cement at 64'. Spotted 50 sacks Thixolite, 2# Permacheck, 1/2# celloseal & 3% CaCl. PD 7:30 AM 8-13-81. WOC 45 minutes. Ran 1". Tagged cement at 64'. Spotted 100 sacks Class "C" Neat. PD 8:50 AM 8-13-81. Cement circulated 5 sacks to pit. WOC 21 hours. Nipped up & tested to 1000 psi, OK. Reduced hole to 7-7/8". Drilled plug & resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W. C. Anderson

TITLE Engineering Secretary

DATE 8-21-81

APPROVED BY W. C. Anderson

TITLE OIL AND GAS INSPECTOR

DATE AUG 26 1981

CONDITIONS OF APPROVAL, IF ANY: