Drawer DD	Form Approved.
UNITED STATES ^{Artesia} , NM 88210	Budget Bureau No. 42-R1424
DEPARTMENT OF THE INTERIOR	5. LEASE RECEIVED
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
GEOLOGICAL SORVET	JAN 2 4 1983
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
Do not use this form for proposals to drill or to deepen or plug back to a different iservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME APTESIA OFFICE
servoir. Use Form 9–331–C for such proposals/	8. FARM OR LEASE NAME ARTESIA, OFFICE McClellan-Harris Federal
1. oil 🕅 gas 🗆 other	9. WELL NO.
2. NAME OF OPERATOR	1
McClellan Oil Corporation	10. FIELD OR WILDCAT NAME S. Lucky Lake - Queen
3. ADDRESS OF OPERATOR	11. SEC., T., R., M., OR BLK. AND SURVEY OR
P.O. Drawer 730 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
below.)	Sec. 21-T15S-R29E 12. COUNTY OR PARISH 13. STATE
AT SURFACE: 330" FIL & 2310 FWL AT TOP PROD. INTERVAL:	N M
AT TOTAL DEPTH:	14. API NO.
6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 3823.3' G.L.
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	3823.3 0.2.
	· · · · ·
SHOOT OR ACIDIZE	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
	change on Form 9-350.)
MULTIPLE COMPLETE	
ABANDON* Cother) Casing & cement	
(other) Lasting & Cement 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly sta	the stimut details and give pertinent dates
17 DESCRIPT PROPOSED OR COMPLETED OPERATIONS (Clearly sta	te all pertinent uctans, and give potentions and
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly sta including estimated date of starting any proposed work. If well is of measured and true vertical depths for all markers and zones pertine	
including estimated date of starting any proposed work. If were a measured and true vertical depths for all markers and zones pertine 1-12-83: Move in Yucca Rig #1. Spud with 1	nt to this work.)* $2\frac{1}{4}$ " bit.
1 12/82. Drilled to 335' Ran 331.45' of 8	$2\frac{1}{4}$ " bit. $2\frac{1}{4}$ " bit. 3-5/8", 20 1b/ft casing.
1-12-83: Move in Yucca Rig #1. Spud with 1 1-13/83: Drilled to 335'. Ran 331.45' of 8	nt to this work.)* .2¼" bit. 3-5/8", 20 lb/ft casing. th 2% CaCl2. Ready mixed
<pre>including estimated date of starting any proposed work. If work is ' measured and true vertical depths for all markers and zones pertine 1-12-83: Move in Yucca Rig #1. Spud with 1 1-13/83: Drilled to 335'. Ran 331.45' of 8 Cemented with 200 sx Class "C" wit with 2% CaCl2. WOC - 18 hours. Not starting any proposed work. If work is ' including estimated date of starting any proposed work. If work is ' including estimated date of starting any proposed work. If work is ' measured and true vertical depths for all markers and zones pertine 1-12-83: Move in Yucca Rig #1. Spud with 1 1-13/83: Drilled to 335'. Ran 331.45' of 8 Cemented with 200 sx Class "C" with</pre>	nt to this work.)* .2¼" bit. 3-5/8", 20 1b/ft casing. th 2% CaCl2. Ready mixed
1-12-83: Move in Yucca Rig #1. Spud with 1 1-13/83: Drilled to 335'. Ran 331.45' of 8	nt to this work.)* .2¼" bit. 3-5/8", 20 1b/ft casing. th 2% CaCl2. Ready mixed
<pre>including estimated date of starting any proposed work. If works of measured and true vertical depths for all markers and zones pertine 1-12-83: Move in Yucca Rig #1. Spud with 1 1-13/83: Drilled to 335'. Ran 331.45' of 8 Cemented with 200 sx Class "C" wit with 2% CaCl2. WOC - 18 hours. Not all the starting and the startin</pre>	nt to this work.)* .2¼" bit. 3-5/8", 20 1b/ft casing. th 2% CaCl2. Ready mixed
<pre>including estimated date of starting any proposed work. If works of measured and true vertical depths for all markers and zones pertine 1-12-83: Move in Yucca Rig #1. Spud with 1 1-13/83: Drilled to 335'. Ran 331.45' of 8 Cemented with 200 sx Class "C" wit with 2% CaCl2. WOC - 18 hours. Not all the starting and proposed work. If works is the starting and proposed work. If work is the starting and the starting and proposed work. If work is the starting and the starting and</pre>	nt to this work.)* .2¼" bit. 3-5/8", 20 1b/ft casing. th 2% CaCl2. Ready mixed
<pre>including estimated date of starting any proposed work. If works of measured and true vertical depths for all markers and zones pertine 1-12-83: Move in Yucca Rig #1. Spud with 1 1-13/83: Drilled to 335'. Ran 331.45' of 8 Cemented with 200 sx Class "C" wit with 2% CaCl2. WOC - 18 hours. Not all the starting and proposed work. If works is the starting and proposed work. If work is the starting and the starting and proposed work. If work is the starting and the starting and</pre>	nt to this work.)* .2¼" bit. 3-5/8", 20 1b/ft casing. th 2% CaCl2. Ready mixed
<pre>including estimated date of starting any proposed work. If works of measured and true vertical depths for all markers and zones pertine 1-12-83: Move in Yucca Rig #1. Spud with 1 1-13/83: Drilled to 335'. Ran 331.45' of 8 Cemented with 200 sx Class "C" wit with 2% CaCl2. WOC - 18 hours. Not all the starting and proposed work. If works is the starting and proposed work. If work is the starting and the starting and proposed work. If work is the starting and the starting and</pre>	nt to this work.)* .2¼" bit. 3-5/8", 20 1b/ft casing. th 2% CaCl2. Ready mixed
<pre>including estimated date of starting any proposed work. In Works of measured and true vertical depths for all markers and zones pertine 1-12-83: Move in Yucca Rig #1. Spud with 1 1-13/83: Drilled to 335'. Ran 331.45' of & Cemented with 200 sx Class "C" wit with 2% CaCl₂. WOC - 18 hours. N Drilled out with 7-7/8" bit.</pre>	nt to this work.)* .2¼" bit. 3-5/8", 20 lb/ft casing. th 2% CaCl ₂ . Ready mixed NU BOP and rotating head.
Including estimated date of starting any proposed work. In Works of measured and true vertical depths for all markers and zones pertine 1-12-83: Move in Yucca Rig #1. Spud with 1 1-13/83: Drilled to 335'. Ran 331.45' of & Cemented with 200 sx Class "C" with with 2% CaCl2. WOC - 18 hours. No Drilled out with 7-7/8" bit. Subsurface Safety Valve: Manu. and Type	nt to this work.)* .2¼" bit. 3-5/8", 20 lb/ft casing. th 2% CaCl ₂ . Ready mixed NU BOP and rotating head.
 including estimated date of starting any proposed work. In Works of measured and true vertical depths for all markers and zones pertine 1-12-83: Move in Yucca Rig #1. Spud with 1 1-13/83: Drilled to 335'. Ran 331.45' of 8 Cemented with 200 sx Class "C" with with 2% CaCl2. WOC - 18 hours. No Drilled out with 7-7/8" bit. Subsurface Safety Valve: Manu. and Type	nt to this work.)* .2¼" bit. 3-5/8", 20 lb/ft casing. th 2% CaCl ₂ . Ready mixed NU BOP and rotating head.
 Subsurface Safety Valve: Manu. and Type Subsurface Safety Valve: Manu. and Type I hereby certify that the foregoing is true and correct Manual Time Operations. 	nt to this work.)* .2¼" bit. 3-5/8", 20 lb/ft casing. th 2% CaCl ₂ . Ready mixed NU BOP and rotating head.
 including estimated date of starting any proposed work. If Went's reasured and true vertical depths for all markers and zones pertine 1-12-83: Move in Yucca Rig #1. Spud with 1 1-13/83: Drilled to 335'. Ran 331.45' of 8 Cemented with 200 sx Class "C" with with 2% CaCl2. WOC - 18 hours. No Drilled out with 7-7/8" bit. Subsurface Safety Valve: Manu. and Type	ManagepateJanuary 14, 1983
Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED ACCEPTED FOR EFCORD (ORIG. SGD.) DAVID R. GLASS	ManagepateJanuary 14, 1983
including estimated date of starting any proposed work. If Went's measured and true vertical depths for all markers and zones pertine 1-12-83: Move in Yucca Rig #1. Spud with 1 1-13/83: Drilled to 335'. Ran 331.45' of & Cemented with 200 sx Class "C" with with 2% CaCl ₂ . WOC - 18 hours. M Drilled out with 7-7/8" bit. Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED	Ant to this work.)* .2¼" bit. 3-5/8", 20 1b/ft casing. th 2% CaCl ₂ . Ready mixed NU BOP and rotating head. Set @Fi ManagepareJanuary_14, 1983 office use)
Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED ACCEPTED FOR EFCORD (ORIG. SGD.) DAVID R. GLASS	Set @F ManagepareJanuary 14, 1983
including estimated date of starting any proposed work. If were in measured and true vertical depths for all markers and zones pertine 1-12-83: Move in Yucca Rig #1. Spud with 1 1-13/83: Drilled to 335'. Ran 331.45' of & Cemented with 200 sx Class "C" with with 2% CaCl ₂ . WOC - 18 hours. M Drilled out with 7-7/8" bit. Subsurface Safety Valve: Manu. and Type	Ant to this work.)* .2¼" bit. 3-5/8", 20 1b/ft casing. th 2% CaCl ₂ . Ready mixed NU BOP and rotating head. Set @ F ManagepateJanuary_14, 1983 office use)
<pre>including estimated date of starting any proposed work. If were reasured and true vertical depths for all markers and zones pertine 1-12-83: Move in Yucca Rig #1. Spud with 1 1-13/83: Drilled to 335'. Ran 331.45' of & Cemented with 200 sx Class "C" wit with 2% CaCl2. WOC - 18 hours. N Drilled out with 7-7/8" bit. Subsurface Safety Valve: Manu. and Type</pre>	Managepate

Į