

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER 10  
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Mesa Petro Corp.</u>		Lease <u>Mesa St. Com.</u>		Well # <u>4</u>	
Location of Well	Unit <u>K</u>	Section <u>32</u>	Township <u>15</u>	Range <u>28</u>	County <u>Gad.</u>
Drilling Contractor	Type of Equipment <u>Rotary</u>				

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement

Casing Data:

Surface \_\_\_\_\_ joints of \_\_\_\_\_ inch \_\_\_\_\_ # Grade \_\_\_\_\_  
(Approved) (Rejected) \_\_\_\_\_

Inspected by \_\_\_\_\_ date \_\_\_\_\_

Cementing Program

Size of hole 12 1/4" Size of Casing 8 5/8" Sacks cement required \_\_\_\_\_

Type of Shoe used guide Float collar used Insert Btm 3 jts welded yes

TD of hole 1865' Set 1865' Feet of 8 5/8" Inch 32 # Grade J-55

New-used csg. @ 1865' with 1100 sacks neat cement around shoe

+ \_\_\_\_\_ sax \_\_\_\_\_ additives \_\_\_\_\_

Plug down @ 9:00 (AM) (PM) Date 5/31/85

Cement circulated yes No. of Sacks 125 sa

Cemented by Western Co. Witnessed by Mike Stubblefield

Temp. Survey ran @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_ top cement @ \_\_\_\_\_

Casing test @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method Used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Checked for shut off @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Remarks: Operator encountered Wt. flow 1st flow 468'-500' 160 BWPH  
2nd on 530'-35' 20 BWPH

Level 1450'