

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 100
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Gates Petr. Corp.</u>		Lease <u>Little Cuevo Ut</u>		Well # <u>2</u>	
Location of Well	Unit <u>C</u>	Section <u>33</u>	Township <u>17 S</u>	Range <u>18 E</u>	County <u>Chaves</u>
Drilling Contractor	<u>Young Drilg. Rig #4</u>		Type of Equipment <u>Rotary</u>		
* Witness <u>APPROVED CASING PROGRAM</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>17 1/2</u>	<u>13 3/8</u>	<u>48# H-40</u>		<u>400</u>	<u>300 Circ</u>
<u>12 1/4</u>	* <u>9 5/8</u>	<u>36# K-55</u>		<u>1250</u>	<u>500 Circ</u>
<u>7 7/8</u>	<u>5 1/2</u>	<u>15.5# K-55</u>		<u>TD</u>	<u>1300</u>
Casing Data:					
Surface _____ joints of _____ inch _____ # Grade _____					
(Approved) (Rejected) _____					
Inspected by _____ date _____					
Cementing Program					
Size of hole <u>12 1/4</u> Size of Casing <u>8 5/8</u> Sacks cement required <u>200</u>					
Type of Shoe used <u>Tex-Met</u> Float collar used <u>Insert</u> Btm 3 jts welded <u>yes</u>					
TD of hole <u>1225</u> Set <u>1227</u> Feet of <u>8 5/8</u> Inch <u>24</u> # Grade <u>K-55</u>					
New- used csg. @ <u>1227</u> with <u>200</u> sacks neat cement around shoe					
+ <u>500</u> sax <u>Pace Setter lite</u> additives <u>#10 Celoflake 3% cc</u>					
Plug down @ <u>4:00</u> (AM) (PM) Date <u>7-7-85</u>					
Cement circulated <u>yes</u> No. of Sacks <u>30</u>					
Cemented by <u>Western</u> Witnessed by <u>BW Weaver</u>					
Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____					
Casing test @ _____ (AM) (PM) Date _____					
Method Used _____ Witnessed by _____					
Checked for shut off @ _____ (AM) (PM) Date _____					
Method used _____ Witnessed by _____					
Remarks: _____					