

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	☒
FILE	☒
U.S.G.S.	
LAND OFFICE	
OPERATOR	☒

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

RECEIVED BY

JUL 11 1986

O. C. D.

Form C-103
Revised 10-1

5a. Indicate Type of Lease

State ☐

Fee ☒

5. State Oil & Gas Lease No.

N/A

SUNDRY NOTICES AND REPORTS OF WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR RE-ENTER OR PLUG WELLS TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐ GAS WELL ☒ OTHER ☐

7. Unit Agreement Name

N/A

8. Farm or Lease Name

HAMS

9. Well No.

1

10. Field and Pool, or Wildcat

Wildcat - Penn.

UNIT LETTER E 1980 FEET FROM THE North LINE AND 660 FEET FROM

THE West LINE, SECTION 22 TOWNSHIP 15S RANGE 25E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)

3460' GR

12. County

Chaves

6. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐

CHANGE PLANS ☐

CASING TEST AND CEMENT JOB ☐

OTHER Also, enclosing DST reports.

OTHER ☐

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1503.

Started plugging @ 11:00 a.m., 07/08/86. Set 100' plugs 50' in and 50' out at the following tops:

Plug #1 - 35 sx Class "H" cement - Mississippian 6685'

Plug #2 - 50 sx Class "H" cement - Penn 1 5950'

Plug #3 - 55 sx Class "H" cement - Wolfcamp Line 5115'

Plug #4 - 35 sx Class "H" cement - ABO 3950'

Plug #5 - 35 sx Class "H" cement - Tubb 3230'

Plug #6 - 35 sx Class "H" cement - Glorietta 1740'

Plug #7 - 45 sx Class "H" cement - 8-5/8" casing shoe - 1045'

Plug #8 - 35 sx Class "H" cement - 13-3/8" casing shoe - 685'

Surface Plug - 20 sx Class "H" cement.

WO cement 3 hrs at each casing shoe plug. Went in hole and tagged each casing shoe plug. All plugs set with Class "H" cement, using Mud Laden Drilling fluid, (9.8# p/gallon). RIG RELEASED @ 5:00 a.m., 07/09/86.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

WITNESSED Brenda K. Godfrey

TITLE Production Analyst

DATE 07/10/86

APPROVED BY Danell Moore

TITLE Geologist

DATE 12/3/87

CONDITIONS OF APPROVAL, IF ANY:

Post TD-2
1-23-87
P+A