

4/5F
OFF

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

L-949

7. Lease Name or Unit Agreement Name

State "ET"

8. Well No.

2

9. Pool name or Wildcat

Diamond Mound ATONA MOUNTAIN

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☒

OTHER

FEB 02 '89

2. Name of Operator

FORAN OIL COMPANY ✓

O. C. D.
ARTESIA, OFFICE

3. Address of Operator

801 S. Fillmore Suite 450 Amarillo, Texas 79101

4. Well Location

Unit Letter L : 1980 Feet From The South Line and 660 Feet From The West Line

Section 36 Township 15 South Range 27 East NMPM Chaves County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3598' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Operator drilled 12 1/4" hole from 350' to a depth of 1800'. No loss of circulation was encountered. Ran 52 Joints of 8 5/8" 24# J-55 ST&C R-3 casing. Texas pattern guide shoe set @ 1800', Float collar @ 1768'.

Cemented with 650 sx. Pacemaker Lite, (Wt.--12.4#/gal, Yield--1.98 ft³), Tailed with 300 sx. Class "C" + 2% CaCl₂. (Wt.--14.8#/gal, Yield--1.32 ft³.) Bump plug with 1000#. Float held OK. Circulated 100 sx. cement to the pit. Plug down at 3:15 PM MST 1-8-89. WOC 12 hours and test casing and BOP to 1000# for 30 min & held OK.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE H. E. Gene Lee

TITLE Agent

DATE 1-11-89

TYPE OR PRINT NAME H. E. Gene Lee

TELEPHONE NO. 622-7355

(This space for State Use)

Original Signed By
Mike Williams

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

FEB 09 1989