	CIST
Submit 3 Copies To Appropriate Distince 1011 - 73 State of New Mexico	Form C-103
Energie Minerols and Natural Resources	Revised March 25, 1999
District I 1625 N. French Dr., Hobbs, XH 88240	WELL API NO.
District II	30-005-63313
District III 1220 South St. Francis Dr.	5. Indicate Type of Lease
1000 Rio Brazos Rd., Aztec, NM 87410 Santa Fe, NM 87505	STATE X FEE 6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM	0. State Off & Gas Lease NO. V-4459
SUNDRY SCREES ADD REPORTS ON WELLS	7. Lease Name or Unit Agreement Name:
(DO NOT USE THIS FORM FOR PEOPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well:	Windmill ATI State
Oil Well Gas Well X Other	
2. Name of Operator	7. Well No.
Yates Petroleum Corporation	#4
3. Address of Operator	8. Pool name or Wildcat
105 S. 4 th Street Artesia, NM 88210	Buffalo Valley Penn
4. Well Location	
Unit Letter <u>L: 1650</u> feet from the <u>South</u> line and <u>660</u> feet from the <u>West</u> line	
Section 16 Township 15S Range 28E	NMPM Chaves County
10. Elevation (Show whether DR, RKB, RT, GR,	etc.)
3570' GR	
11. Check Appropriate Box to Indicate Nature of Notic	
NOTICE OF INTENTION TO: SU	
PULL OR ALTER CASING DULTIPLE CASING TEST COMPLETION	AND
Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of	
starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.	
12/4/00 – Spud 22" hole with rathole machine at 11:00 AM. Set 40' of 16" conductor pipe, cemented to	
surface. Notified Mae Morgan with Artesia OCD of spud.	
12/6/00 – Resumed drilling with rotary tools, 14-3/4" hole, at 11:00 PM. 12/7/00 – TD of 14-3/4" hole at 7:00 AM at 400'.	
Ran 9 joints 11-3/4" 42# H-40 8R ST&C casing set at 400'.	
Texas pattern notched guide shoe set at 400'. Insert float set at 355'.	
Cemented with 200 sxs Premium Plus C + ¼ pps flocele + 2% CaCl2 (yld 1.34, wt 14.8). Tailed in with 150 sxs C +	
2% CaCl2 (yld 1.34, wt 14.8). PD at 12:00 PM. Bumped plug to 500 psi, held OK. Circ 21 sxs . WOC.	
12/8/00 – Drilled out at 9:00 AM. WOC 21 hours.	
Reduced hole to 11" and resumed drilling.	
I hereby certify that the information above is true and complete to the best of my know	/ledge and belief.
SIGNATURE Main Huge TITLE Engineering Te	echnician DATE April 2, 2002
Type or print name Sugar Herpin	Telephone No. 505-748-1471
(This space for State used / ORIGINAL SIGNED BY TIM W. CUM	APR 0 5 2002
APPPROVED BY	DATE

Conditions of approval, if any:

AN INDER THE REPORT OF THE

藏电。 14