	C15 F
Submit 3 Copies To Appropriate District 2017 Office State of New Mexico	Form C-103
Bearing Minerals and Natural Peccurage	Revised March 25, 1999 WELL API NO.
District I 1625 N. French Dr., Hobbs, NM 80240 District II 811 South First, Artesiar NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 88210 Santa Fe, NM 87505	30-005-63313
811 South First, Artesia, NM 88210 CONSERVATION DIVISION	5. Indicate Type of Lease
District III 1000 Rio Brazos Rd., Aztec, NM 8840 District IV Santa Fe, NM 87505	STATE X FEE
District IV 1220 S. St. Francis Dr., Santa Fe, No.	6. State Oil & Gas Lease No.
87505	V-4459
SUNDRES OF SAND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well:	7. Lease Name or Unit Agreement Name: Windmill ATI State
Oil Well Gas Well X Other	
2. Name of Operator	7. Well No.
Yates Petroleum Corporation	#4 8. Pool name or Wildcat
3. Address of Operator 105 S. 4th Street Artesia, NM 88210	Buffalo Valley Penn
105 3. 4 ··· Silleer Allesia, NW 662 To	Bolidio Valley I etili
4. Well Location	
TY IV I A 1/FO C (C) South line and //O Southern Nort line	
Unit Letter L: 1650 feet from the South line and 660 feet from the West line	
Section 16 Township 15S Range 28E NMPM Chaves County	
10. Elevation (Show whether DR, RKB, RT, GR, etc.)	
3570' GR	
11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: ALTERING	
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WOR	CASING DIVIDING CASING
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRI	LLING OPNS. ABANDONMENT
PULL OR ALTER CASING MULTIPLE CASING TEST AN CEMENT JOB	ND
	cement intermediate casing X
Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.	
12/10/00 – Reached TD of 11" hole at 1912' at 5:30 AM.	
Ran 46 joints (1916') 8-5/8" 24# J-55 casing set at 1911'.	
Regular guide shoe set at 1911'. Float collar set at 1868.5'. Cemented with 400 sxs Interfill C + 1/4 pps flocele (yld 2.46, wt 11.9). Tailed in with 200 sxs C + 2% CaCl2 (yld 1.32	
wt 14.8). PD at 3:15 PM. Bumped plug to 850 psi, held OK. Circ 58 sxs. WOC.	
12/11/00 – Drilled out at 9:15 PM. WOC 18 hours.	
Reduced hole to 7-7/8" and resumed drilling.	
I hereby certify that the information above is true and complete to the best of my knowled	loe and helief
1 Tree-by certify that the information above is true and complete to the best of my knowledge and benefit	
SIGNATURE Missing the TITLE Engineering Technician DATE April 2, 2002	
Type or print name Susan Herpin	Telephone No. 505-748-1471
(This space for State use)	
APPPROVED BY THE WAR BUNG	APR 0 5 2902
Conditions of approval, if any:	