

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

WELL API NO.

30-005-63313

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

V-4459

7. Lease Name or Unit Agreement Name:

Windmill ATI State

7. Well No.

#4

8. Pool name or Wildcat

Buffalo Valley Penn

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM 101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 S. 4th Street Artesia, NM 88210

4. Well Location

Unit Letter L : 1650 feet from the South line and 660 feet from the West line

Section 16 Township 15S Range 28E NMPM Chaves County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3570' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Set cement plugs in lost circulation zone ☒

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

12/13/00 - Lost returns at 2816'. Circulate for DST #1 with no returns.

Run DST #1 2772-2826' San Andres.

12/14/00 - Drilled to 2850', no returns. Pump LCM sweeps, no returns.

TIH open ended. Set cement plug #1 at 2769' with 200 sxs C + 2% CaCl2 + 5 pps gilsonite + 1/3 pps FC. WOC.

Try to load hole - no tag. Set cement plug #2 at 2769' with 100 sxs Thixad + 2% CaCl2 + 10 pps gilsonite + 1/4 pps FC and 100 sxs C + 2% CaCl2 + 5 pps gilsonite. WOC. Try to load hole - no returns.

12/15/00 - TIH to tag cement - no cement. Set cement plug #3 with 200 sxs Thixad + 2% CaCl2 + 10 pps gilsonite + 1/4 pps FC. WOC. TIH to tag cement - no cement.

Set cement retainer at 1814'. Cement with 325 sxs H + 2% CaCl2. No pressure. Sting out of retainer and reverse out, no cement. Left 640 psi on loss zone, zone holding. WOC.

12/16-12/17/00 - Drilled out retainer. Drilled cement 2229-2850' with full returns.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Susan Herpin TITLE Engineering Technician DATE April 2, 2002

Type or print name Susan Herpin

Telephone No. 505-748-1471

(This space for State use) **ORIGINAL SIGNED BY TIM W. GUM**

DISTRICT II SUPERVISOR

APPROVED BY [Signature] TITLE _____ DATE APR 05 2002

Conditions of approval, if any

