		.10	, <i>U</i>	
Submit 3 Copies To Appropriate District Office	State of New Me		- and	Form C-103
District I 1625 N. French Dr., Hobbs, NM 88240	Energy, Minerals and Natural Resources		WELL API NO.	Revised March 25, 1999
District II 811 South First, Artesia, NM 88210 OIL CONSERVATION DIVISION			30-005-63396	
District III 1220 South St. Francis Dr.		5. Indicate Type of Lease STATE X FEE		
1000 Rio Brazos Rd., Aztec, NM 87410Santa Fe, NM 87505District IVSanta Fe, NM 87505		6. State Oil & G		
1220 S. St. Francis Dr., Santa Fe, NM 87505			VO-5373	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A			7. Lease Name or	Unit Agreement Name:
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			Chester AYC :	State
1. Type of Well:				
Oil Well Gas Well X   2. Name of Operator	Other	<b>A</b>	7. Well No.	
Yates Petroleum Corpor	ation 🦯		#1	
3. Address of Operator   105 S. 4th Street   Artesia, NM 88210   RECEIVED   8. Pool name or Wildca     Buffalo Valley P				
105 S. 4" Sheer Aries		O - ARTESIA	Βυπαίο να	lley renn
4. Well Location				
Unit Letter N: 660 feet from the South line and 1650 feet from the West line				
Section <b>9</b>	Township15SRange10.Elevation (Show whether DI	<b>28E</b> NM R RKR RT GR etc		County
3565' GR				
11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data				
			SEQUENT REI	PORT OF:
	PLUG AND ABANDON	REMEDIAL WORI	K 🗌	
	CHANGE PLANS	COMMENCE DRILLING OPNS. X PLUG AND ABANDONMENT		
PULL OR ALTER CASING		CASING TEST AN CEMENT JOB	1D	
OTHER:		OTHER:		
Describe proposed or completed or				
starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.				
7/3/01 – Spud 26" hole at 1:00 PM with rathole machine. Set 40' of 20" conductor pipe, cemented to surface.				
Notified Jerry Guy with Artesia OCD. 7/6/01 – Resumed drilling with 14-3/4" hole with rotary tools at 10:30 AM.				
Reached TD of surface hole at 417'.				
7/7/01 – Ran 10 joints (423.21') 11-3/4" 42# H40 casing set at 417'. Texas pattern notched guide shoe set at 417'. Insert float set at 375'. Cemented with 150 sxs P + 2% CC + 10% Cal-seal + 5 pps gilsonite + ¼ pps flocele				
(yid 1.54, wt 14.4). Tailed in with 250 sxs Premium Plus + $2\%$ CC + $10\%$ Cd-sedi + 5 pps glisonite + $2\%$ pps hocele				
to 530 psi, held OK. Circ 94 sxs. WOC.				
7/8/01 – Drilled out at 3:30 AM. WOC 21 hours 15 mins. Reduced hole to 11" and resumed drilling.				
I hereby certify that the information above is true and complete to the best of my knowledge and belief.				
SIGNATURE My Min Minpon TITLE Engineering Technician DATE January 17, 2002				
Type or print name Susan He	rpin		Telephone	No. 505-748-1471
(This space for State use)	BNED BY TIM W. GUN			JAN 2 8 2002
APPPROVED BY <b>DISTRICT II S</b> Conditions of approval, if any:				DATE