			- ( )	
Submit 3 Copies To Appropriate District	State of New Me	exico C		Form C-103
Office <u>District I</u>	Energy, Minerals and Natu	aral Resources	WELL API NO.	Revised March 25, 1999
1625 N. French Dr., Hobbs, NM 88240 District II	OU CONCERNATION DRUGION		<b>30-005-63396</b>	
811 South First, Artesia, NM 88210 District III	OIL CONSERVATION DIVISION 1220 South St. Francis Dr.		5. Indicate Type of	of Lease
1000 Rio Brazos Rd., Aztec, NM 87410	Santa Fe, NM 87505		STATE 7	K FEE
District IV 1220 S. St. Francis Dr., Santa Fe, NM	Santa PC, NW 87505		6. State Oil & G	as Lease No.
87505	TER AND DEBORTS ON WELL	7	VO-5373	Unit Agreement Name:
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A			7. Lease Name of	Olin Agreement Name.
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			Chester AYC S	State
1. Type of Well:		Â.		
Oil Well Gas Well X	Other	<u> </u>	7. Well No.	
2. Name of Operator Yates Petroleum Corpor	ation	Dros	# <b>1</b>	
3. Address of Operator	01	RECEIVED	8. Pool name or	Wildcat
105 S. 4 <sup>th</sup> Street Artesi	ia, NM 88210	ANTESIA	Buffalo Va	lley Penn
4. Well Location			1	
4. Well Location				
Unit Letter <u>N</u> : <u>6</u>	60 feet from the South	line and <b>1650</b>	feet from the	West line
Section <b>9</b>	Township <b>15S</b> Range	<b>28E</b> NM	PM Chaves	County
Section <b>9</b>	10. Elevation (Show whether D			County
3565' GR				
	ppropriate Box to Indicate N			
NOTICE OF IN	TENTION TO:	SUB	SEQUENT REI	
	PLUG AND ABANDON	REMEDIAL WORK		
	CHANGE PLANS	COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT		
PULL OR ALTER CASING	MULTIPLE COMPLETION	CASING TEST AND CEMENT JOB		
OTHER:		OTHER: set and	cement intermedicat	e casing X
Describe proposed or completed op				
starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or				
recompilation. 7/12/01 – Reached TD of 11" hole at 3285' at 5:45 PM. Log well. Logger's TD 3290'.				
7/13/01 – Ran 78 joints (3295.6	3') 8-5/8" 32# J-55 casing se	et at 3285'. Regu	lar guide shoe se	t at 3285'. Float
collar set at 3239.12'. Cemented with 540 sxs Interfill C + 5 pps gilsonite (yld 2.42, wt 11.9). Tailed in with 200 sxs				
P + C with 2% CaCl2 (yld 1.34, wt 14.8). PD at 7:00 PM. Bumped plug to 1300 psi, held OK. Circ 135 sxs. WOC.				
7/14/01 – Drilled out at 4:30 PM. WOC 21 hours 30 mins. Reduced hole to 7-7/8" and resumed drilling.				
I hereby certify that the information	above is true and complete to the	e best of my knowled	ige and belief.	
SIGNATURE Main III	iperTITLEE	ingineering Tec	hnician_DATE_	January 17, 2002
Type or print name Sysan He	rpin		Telephone	No. 505-748-1471
(This space for State ise ORIGINAL SIGNED BY TIM W GILL				
APPPROVED BY AND THE DALAN 2 8 202				
ATTROVED DI // ·····				

Conditions of approval, if any: