

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES  
LOCATE WELL CORRECTLY

T. E. Boggs

Boggs

Well No. 112 Company or Operator SE NW of Sec. 5 Lease 168  
R. 25, N. M. P. M., Wildcat Field, Eddy County.  
Well is 3151 feet south of the North line and 2309 feet east west of the East line of 5-168-892  
If State land the oil and gas lease is No. \_\_\_\_\_ Assignment No. \_\_\_\_\_  
If patented land the owner is T. E. Boggs, Address Roswell, N. M.  
If Government land the permittee is \_\_\_\_\_, Address \_\_\_\_\_  
The Lessee is \_\_\_\_\_, Address \_\_\_\_\_  
Drilling commenced 12-1-48 19\_\_\_\_ Drilling was completed 10-19-49 19\_\_\_\_  
Name of drilling contractor \_\_\_\_\_, Address \_\_\_\_\_  
Elevation above sea level at top of casing 3507 feet.  
The information given is to be kept confidential until \_\_\_\_\_ 19\_\_\_\_.

OIL SANDS OR ZONES

No. 1, from \_\_\_\_\_ to \_\_\_\_\_ No. 4, from \_\_\_\_\_ to \_\_\_\_\_  
No. 2, from \_\_\_\_\_ to \_\_\_\_\_ No. 5, from \_\_\_\_\_ to \_\_\_\_\_  
No. 3, from \_\_\_\_\_ to \_\_\_\_\_ No. 6, from \_\_\_\_\_ to \_\_\_\_\_

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from \_\_\_\_\_ to \_\_\_\_\_ feet. \_\_\_\_\_  
No. 2, from \_\_\_\_\_ to \_\_\_\_\_ feet. \_\_\_\_\_  
No. 3, from \_\_\_\_\_ to \_\_\_\_\_ feet. \_\_\_\_\_  
No. 4, from \_\_\_\_\_ to \_\_\_\_\_ feet. \_\_\_\_\_

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
	<u>8"</u>	<u>737</u>	<u>set</u>			
	<u>5"</u>	<u>751</u>	<u>"</u>			
	<u>5-1/2"</u>	<u>855</u>	<u>"</u>			

PLUGS AND ADAPTERS

Heaving plug—Material \_\_\_\_\_ Length \_\_\_\_\_ Depth Set \_\_\_\_\_  
Adapters—Material \_\_\_\_\_ Size \_\_\_\_\_

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from \_\_\_\_\_ feet to \_\_\_\_\_ feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet.  
Cable tools were used from \_\_\_\_\_ feet to \_\_\_\_\_ feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet.

PRODUCTION

Put to producing \_\_\_\_\_, 19\_\_\_\_  
The production of the first 24 hours was \_\_\_\_\_ barrels of fluid of which \_\_\_\_\_ % was oil; \_\_\_\_\_ % emulsion; \_\_\_\_\_ % water; and \_\_\_\_\_ % sediment. Gravity, Be \_\_\_\_\_  
If gas well, cu. ft. per 24 hours \_\_\_\_\_ Gallons gasoline per 1,000 cu. ft. of gas \_\_\_\_\_  
Rock pressure, lbs. per sq. in. \_\_\_\_\_

EMPLOYEES

\_\_\_\_\_, Driller \_\_\_\_\_, Driller  
\_\_\_\_\_, Driller \_\_\_\_\_, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 19<sup>th</sup>  
day of May, 1951  
[Signature]  
Notary Public  
My Commission expires Jan. 26, 1954.

Roswell, N. M. May 15, 1951  
Name [Signature] Place \_\_\_\_\_ Date \_\_\_\_\_  
Position Owner  
Representing T. E. Boggs  
Company or Operator.  
Address Roswell, N. M.

# FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
781	796	15	Anhy & Dolo
796	802	8	Anhy & Dolo
802	825	23	Anhy & Dolo
825	831	6	Anhy & Dolo
831	852	21	Sandy Dolo
852	857	5	Sandy Dolo
857	860	3	Anhy & Dolo
860	873	13	Anhy & Dolo
873	892	19	Anhy & sugary Dolo
892	899	7	Dense Anhy & Dolo
899	902	3	Fine Anhy & Dolo
902	905	3	Oyp & Fine Dolo
	TD 1200'	Dolo	