

13 Sept 1961
7-41152
10 1-06 2.0169 per 28.

plus in bottom

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESTA, NEW MEXICO

FIELD REPORT FOR ^{PLUGGING} CEMENTING OF WELLS

Operator <u>N. GORDON PHILLIPS</u>		Lease <u>HEIDBRINK + BARGER</u>		Well # <u>1</u>	
Location of Well	Unit <u>H</u>	Section <u>23</u>	Township <u>17S</u>	Range <u>25E</u>	County <u>DOY</u>
Drilling Contractor	<u>MILLER BROS.</u>		Type of Equipment <u>CABLE TOOLS</u>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>12 1/2</u>	<u>10"</u>				
<u>12 1/2</u>	<u>10"</u>		<u>USED</u>	<u>700</u>	<u>NOHIF</u>
<u>10</u>	<u>8 5/8</u>	<u>32 H</u>	<u>USED</u>	<u>1100</u>	<u>CIRC.</u>

Casing Data:
Surface 15 joints of 5 1/4 inch 17 # Grade TS 50 20
(Approved) (Rejected)
Inspected by J. H. [unclear] date 7-15-61

Cementing Program
Size of hole _____ Size of Casing _____ Sacks cement required _____
Type of Shoe used _____ Float collar used _____ Btm 3 jts welded _____
TD of hole 1292' Set _____ Feet of _____ Inch _____ # Grade _____
New-used csg. @ _____ with _____ sacks neat cement around shoe
+ _____ sax _____ additives _____
Plug down @ _____ (AM) (PM) Date _____
Cement circulated _____ No. of Sacks _____
Cemented by _____ Witnessed by _____
Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____
Casing test @ _____ (AM) (PM) Date _____
Method Used _____ Witnessed by _____
Checked for shut off @ _____ (AM) (PM) Date _____
Method used _____ Witnessed by [unclear] 7-15-1961

Remarks: 1 plug in 1st interval
then run down with iron pipe plugging

1. 1370 to 1293 - 25 lbs
2. 1100 to 1020 - 25 lbs
3. 730 to 630 - 15 lbs

Bartram's binder

Log

oil sands 1270' to 1288'

water 1100' to 1130

rock plug at 1100'