


NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.D.S.	<input checked="" type="checkbox"/>
LAND OFFICE	<input checked="" type="checkbox"/>
OPERATOR	<input checked="" type="checkbox"/>

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501



Form C-103
Revised 10-1-73

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐ GAS WELL ☐ OTHER ☒ Re-Plug

Name of Operator
Yates Petroleum Corporation (formerly N.G. Phillips, Operator)

Address of Operator
207 South 4th St., Artesia, New Mexico 88210

Location of Well
UNIT LETTER H 1980 FEET FROM THE North LINE AND 660 FEET FROM East THE LINE, SECTION 23 TOWNSHIP 17S RANGE 25E N.M.P.M.

7. Unit Agreement Name
8. Farm or Lease Name
City of Artesia (formerly Heidbrink & Barger)
9. Well No.
1 (Heidbrink & Barger)
10. Field and Pool, or WHdcat
Eagle Creek SA
12. County
Eddy

15. Elevation (Show whether DF, RT, GR, etc.)
3482' GL

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER Re-plug <input checked="" type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Propose to drill out surface plug and first plug (380-430'); set 7" casing at 400', cement (Class "C" Neat) to surface. Tag second plug (1021-1100'). Bring cement up to 650' (100' above top of San Andres). Set plug across casing shoe (350-450'). Set surface plug and dry hole marker. Hole to be circulated with mud laden fluid.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED James S. Brown TITLE Engineer DATE 2-20-84
Original Signed By
Leslie A. Clements
Supervisor District II
APPROVED BY _____ TITLE _____ DATE FEB 28 1984

CONDITIONS OF APPROVAL, IF ANY:

Notify OCD 24 hrs prior to starting operation on this well