

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	<input checked="" type="checkbox"/>
LAND OFFICE	<input checked="" type="checkbox"/>
OPERATOR	<input checked="" type="checkbox"/>

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

RECEIVED

MAR 08 1983

Form C-103  
Revised 10-1-78

O. C. D.  
ARTESIA, OFFICE

5d. Indicate Type of Lease  
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
Name of Operator Yates Petroleum Corporation ✓	8. Farm or Lease Name Gissler "AV"
Address of Operator 207 South 4th St., Artesia, NM 88210	9. Well No. 2
Location of Well UNIT LETTER B 660 FEET FROM THE North LINE AND 1980 FEET FROM THE East LINE, SECTION 23 TOWNSHIP 17S RANGE 25E NMPM.	10. Field and Pool, or Wildcat Caple Creek SA
15. Elevation (Show whether DF, RT, GR, etc.) 3482'	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐ CHANGE PLANS ☐  
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒  
CASING TEST AND CEMENT JOB ☐  
OTHER ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Well was plugged on 3-8-83 as follows:

- 1) Plug was set in open-hole from 1250' to 1441' with 20 sx class C neat cement.
- 2) CIBP was set at 1250' with wireline. Tagged CIBP with tubing: depth correct
- 3) Plug was set from 1010' to 1250' (240' fill) with 25 sx class C neat cement.
- 4) Plug was set from 516' to 756' (240' fill) with 25 sx class C neat cement.
- 5) Surface plug was set with four joints of tubing (to 125' depth) with 35 sx class C neat cement; circulated excess cement to pit.
- 6) P/A marker was installed.

Mike Stubblefield, field representative for NMOC D witnessed above operations.

Post ID-2  
3-31-84  
P&A

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED James L. Brown TITLE Engineer DATE 3-9-83  
APPROVED BY Darryl Brooks TITLE Geologist DATE 6-4-84  
CONDITIONS OF APPROVAL, IF ANY: