

County Eddy Depth 1700' Pool Wildcat*

SCOUT REPORT
NEW MEXICO OIL CONSERVATION COMMISSION

Company Mesa Retailers, Inc. Well No. 1 Lease State

1980 Feet from S. Line 660 Feet from W. Line, Sec. 36 Twp. 16S Rge. 26E

Land State Contractor S. P. Yates Drlg. Co. ^{Combr.} R#CT

Elevation 3319 Spudded 4-9-56 Completed 8-1-56

T. A	T. Tu	Total Depth <u>2440sd</u>	P. B. <u>2370</u>
T. X	T. Full	Top Pay	District <u>7</u>
B. X	T. DR	I.P.	BOPD
T. Del Li	T. Wich A.	Base on	BO
T. Del Sd	T. Abo	Choke:	
T. Y	T. WC	Tubing	@
T. SR	T. Hu	Press:	Tbg. Csg.
T. Q	T. Per-Pe	GOR	Gravity
T. PR	T. Penn	Effective Perfs.;	
T. GB	T. Strawn		
T. SA <u>1080</u>	T. Miss		
T. Glo <u>2372</u>	T. WF		
T. Blby	T. Dev	Acid. Frac & Shooting Record:	
T. CF	T. Sil	From	To

CSG. & CEMENTING RECORD

Size	Feet	Sax Cement
8 5/8	345	25 150
5 1/2	2415	190 400
		390

T. Fuss	From	To
T. Mon	From	To
T. Simp	From	To
T. McK		
T. Ell		
T. G.W.		
T. Gr	SHOWS	
T.	S/	
T.	S/	
T.	S/	
T.	S/	
T.	S/	
T.	S/	

4-11-56	TD 345' anhy, WOC	TD 2440 sd. MO
	TD 1410 li. fsg of collar	Rotary + WOC.
	TD 2440 sd	
	return to 1330' & regained	prep sub. 1595-1630
	circum 1330'	from 16000 gal, run
	of 1830 liane.	2" 1595'
	C 1637-97 run 60' 1606 + li.	TD 2440 sd, PB 2370
	TD 2440 li, Prep to Run 5 1/2	test on pump.

Run in. to TD

Correction on perfs

perf 30h 1596-1606, 20h 1614-1620

subd + fls 220 B.L.O + subd drg.

Mixed in per unit, per 20 B.L.O 12'

Csg press 100#

✓

C 1637-77 rec 60' dolo, being
7' tan to gray, med coarsely xylid dolo w/ tight
vert frac, slightly bleeding sib, occasional
anhyd partgs throughout,

10' tan to gray, very tight, med coarsely
xylid dolo. N.S.

15' AA w/ many large blue-white anhyd
includ + ptgs. N.S.

28' Tan to gray, tight med-coarsely xylid dolo N.S.

TD 2440 sd PB 2370

TD 2440 sd, PB 2370 Per load sd

per 18 B.L.O w/ trace xw 12'

TD 2440 sd, PB 2370 si

✓✓ Rupt to P.A.

✓✓✓

aug 8 TD 2440 sd PB 2370 Temp abnd

perf 32h 2294-2302 subd x wtr w/ shd oil