

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

Plugging
FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>TAFT-Mc GEE</i>		Lease <i>McGee - Sharp</i> BLAINE HAINES		Well # <i>I</i>	
Location of Well	Unit <i>L</i>	Section <i>13</i>	Township <i>17S</i>	Range <i>26E</i>	County <i>EDDY</i>
Plugging Contractor <i>OWEN HAINES</i>		Type of Equipment <i>ROTARY</i>			
<i>in hole</i> <u>APPROVED CASING PROGRAM</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>9 7/8"</i>	<i>7"</i>		<i>USED</i>	<i>1288'</i>	<i>50</i>
<i>Casing cut on pull back 600'</i>			<i>600'</i>		
Casing Data:					
Surface _____ joints of _____ inch # Grade _____ (Approved) (Rejected) _____					
Inspected by _____ date _____					
Cementing Program					
Size of hole _____		Size of Casing _____		Sacks cement required _____	
Type of Shoe used _____		Float collar used _____		Btm 3 jts welded _____	
TD of hole <i>1730</i>		Set _____		Feet of _____ Inch # Grade _____	
New-used csg. @ _____ with _____ sacks neat cement around shoe					
+ _____ sax _____ additives _____					
Plug down @ _____ (AM) (PM) Date _____					
Cement circulated _____			No. of Sacks _____		
Cemented by <i>HALLIBURTON</i>			Witnessed by <i>L. BLEY</i>		
Temp. Survey ran @ _____ (AM) (PM) Date _____			top cement @ _____		
Casing test @ _____ (AM) (PM) Date _____					
Method Used _____			Witnessed by _____		
Checked for shut off @ _____ (AM) (PM) Date _____					
Method used <i>Cement plug VIA TUBING</i> Witnessed by _____					
Remarks: <i>Hole was loaded with heavy mud before plugging plugs as follows</i>					
<i>1. 1726 to 1590 - 25 sks. - 10-20-61</i>					
<i>2. 1300 to 1200 - 20 sks. - 10-20-61</i>					
<i>3. 1090 to 990 - 25 sks. - 10-20-61</i>					
<i>4. 810 to 710 - 25 sks. - 10-20-61</i>					