

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

NMOCC COPY
SUBMIT IN TRIPLI
(Other instructions on re-
verse side)

Copy to SF
Form Approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL ☒ WELL GAS ☐ WELL OTHER ☐ 2. NAME OF OPERATOR Leonard Hatch 3. ADDRESS OF OPERATOR 507 Commerce Bank Bldg. Suite #507 Lubbock, Tx. 79401 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) RECEIVED 14. PERMIT NO. O. C. C.	5. LEASE DESIGNATION AND SERIAL NO. NM025603 6. IF INDIAN, ALLOTTEE OR TRIBE NAME 7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME Travis 9. WELL NO. 6 10. FIELD AND POOL, OR WILDCAT Empire Yates 7-Rivers 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 12 T. 21S R. 27E 12. COUNTY OR PARISH Eddy 13. STATE N.M.
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 990/S 990/S	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☒
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
(Other) ☐	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

2 & A well:

1. Notify USGS 24-hrs. prior.
2. Check 7" csg. to see if loose.
3. Run tog. to 446'
4. Pump 25-sxs. cnt.
5. Tag plug with min. 100' rise & min. 50' inside 7" csg. (set to 430')
6. Load hole with heavy mud.
7. If 7" csg. loose pull (Note #1) (ie-protect cnt. plug.)
8. If pull 7" csg. isolate fresh water zone (170-75') 25-sxs. cnt & tag
9. If not pull 7" csg. pump 25-sxs. cnt. to surface & bond over 7" csg. to well bore.
10. If pull 7" csg. circ. 10-sxs. cnt. surface & bond over 7" csg. to well bore.
11. Set dry hole marker
12. Clean & seal location per regulations.

TD=446
7" csg to 430' (25-sxs.)
open hole 430-469 (39')
fresh water sands
170-75' & 464-46'

RECEIVED

NOV 2 1977

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED W. J. Loney

TITLE Agent

DATE November 1, 1977

(This space for Federal or State office use)

APPROVED BY Joe J. Loney

TITLE ACTING DISTRICT ENGINEER

DATE NOV 2 - 1977

CONDITIONS OF APPROVAL, IF ANY:

Subject to rigging well pad & access road not used.

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well, and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of packing of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO 680-379

WMOCC COLY

RECEIVED

NOV 3 1977

U.S. DEPT. OF THE INTERIOR