

W.C. NESE

SCOUT REPORT
NEW MEXICO
OIL CONSERVATION COMMISSION

#8

tem

(Explosive - Extensive)
Fuel

W

N

Company E. Orcutt

Farm Name F. E. Kepple Well No. 2

Sec. 19 Twp. 17 Range 27 County Eddy

Feet from Line: 2310 N. 1650 S. 1650 E. W.

Elevation 3305 Method Spudder

Contractor C. S. Powell

Spudded 4-3-46 Completed 7-15-46 *Re 3-31-47*

AMOUNT

CASING & CEMENTING RECORD

Size	Feet	Inches	Sax Cement
10"	163		S P
8"	1030		S P
7"	1030		S P
5"	1225		S P
5 1/2"	1225		250

JK →

ACID RECORD

Gals.	TA	TG
2000 gals	TX	TSA
	TCA	TGI
	BX	TYo
	TY	TAbO
	TSR	TPenn
Top Pay 1710	TQ	TOrd

TUBING RECORD

2 1/2	1815
-------	------

SHOOTING RECORD

No. of Quarts	From	To
225	1700	1815
No. of Quarts	From	To
S/w 135 E	S/w 1145 L	S/o 1709-16 ✓
S/w 1175 L	S/w 1138 L	S/o 1739 L ✓
S/w 1175 L	S/w 1166-75 ✓	S/o 1864-70 ✓

PACKER

Date		Date	
4-2-46	RU Spdr	MAY 21	✓
4-7	φ 4.50 A.E. R.B.	MAY 28	TD 1375 L SDO
	Continuing A.E. R.B.		✓ SDO Nobody home
	corrected log		
4-16	1175 L	JUN 18	TD 1375 L
4-22	1175 L		Temp abn. h. not plugged
4-30	φ D 1190 L, UP 1030	10-1-46	Prep to drill. φ 1410
4-7	φ 1195 L	10-8-46	φ 1541, gray shale
	φ 1241 L		TD 1676.0 lime test

1795 L.

10-30

1870

TD 1903 L. 550-1679-1714

550-1725-45, 1790-93

NOV 1

TD 1903 L. Woc on

5 1/2

TD 1903 L. C/o air TD prep to test

TD 1903 L. Prep. to test w/o Tbg

TD 1903 L. Luvalling

400 500

TD 1903 L. PB 1810; Finishing

Re-treated 2000 lbs - 4 out plug;

TD 1903 L. PB 1810 2nd plug

TD 1903 L. PB 1810 3rd plug

TD 1903 L. 001847 + PB 1838 + PB 1825 water is shut off

Prep to seal

Ron Lane will

TD 1903 L. PB 1815 C/o after seal

TD 1903 L. PB 1815 C/o 7 flowed

TD 1903 L. PB 1815 C/o 1715 1600' OI 4

C/o 1712

Prep Tbg to test

TD 1903 L. PB 1815 Test 4 2" TD 1815

TD 1903 L. PB 1815 Prep 51 test

Sealed 50 BOP in 12 hrs
on a day test

TD 1903 L.

PB 1815

I.P. Pump 15 BOPD