

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN 7
(Other instructions on
reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☐		7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Leonard Latch		8. FARM OR LEASE NAME Berry A
3. ADDRESS OF OPERATOR 1317 Texas St. Lubbock, Texas 79401		9. WELL NO. 22
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 2310 ft from # line and 1650 ft. from # line		10. FIELD AND POOL, OR WILDCAT Empire
14. PERMIT NO.		12. COUNTY OR PARISH Eddy
15. ELEVATIONS (Show whether DF, RT, GR, etc.)		13. STATE New Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

Rework well

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Well completed in 1961...Treated 1775' to 2198' w/10,000 acid made a small well
5 1/2" casing set 1775'

Recompleted in Dec. 1965 .. Set drillable plug at 550'
perforated h21-37 and h44-50 treated 1000 acid.
made 1 1/2" HOOD from shallow pay.

proposed rework Nov.1, 1965 to make a gas well.

Squeeze off perforations h21-37 and h44-50 with 50 sacks cement, drill out
cement and drill plug set at 550' set drillable at 1300'. Run cement log.
Perforate and check Queen Sand 1170' to 1200'. We will frac with Approx.
10,000 lbs. Sand.

RECEIVED
OCT 28 1965
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

RECEIVED

OCT 29 1965

D. C. C.
ARTESIA, OFFICE

RECEIVED

OCT 27 1965

18. I hereby certify that the foregoing is true and correct

SIGNED

Charles L. Brown

TITLE

Agent

DATE

10-26-65

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED
OCT 28 1965
T. R. C. BELMONT
ACTING DISTRICT ENGINEER

Subject to cementing behind 5 1/2" log
from present top unit to no
lower than 670 feet from surface.
See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

