


N

AREA 640 ACRES
LOCATE WELL CORRECTLY

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Oil Cons. Comm.
Artesia Office

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

C.L. East and W.M. Gray

Artesia, New Mexico

State B 6041

Company or Operator

Well No.

NWSESE

of Sec.

24

T. 17 S

R. 27 E

N. M. P. M. Empire

Field,

Eddy

County.

Well is 4380 feet south of the North line and 900 feet west of the East line of 24-17-27

If State land the oil and gas lease is No. B 6041 Assignment No.

If patented land the owner is Address

If Government land the permittee is Address

The Lessee is W.M. Gray Address Artesia, N.M.

Drilling commenced May 18, 1949 19 Drilling was completed June 2 49

Name of drilling contractor Address

Elevation above sea level at top of casing feet.

The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 420 to 423 No. 4, from to
No. 2, from 458 to 464 No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 108 to 110 feet. 2
No. 2, from 420 to 423 feet. 3
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
7"00	20#		smis.	406'					production

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
10"	7"	406'	15	Halliburton	Heavy	10 sacks

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet
Cable tools were used from 0 feet to 470 feet, and from feet to feet

PRODUCTION

Put to producing June 15 19 49
The production of the first 24 hours was 15 barrels of fluid of which 100 % was oil; % emulsion; % water; and % sediment. Gravity, Be.
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in.

EMPLOYEES

Kermit Hoover
Boyd Hoover Driller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 21st

Artesia, N.M.

day of November 19 49

Name Marjorie Sanders

Position agent

Representing C.L. East & W.M. Gray

Company or Operator

Address Artesia, N.M.

Notary Public

8/28/53

My Commission expires

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	110	110	Anhydrite and surface
110	112	2	water
112	140	28	anhydrite
140	180	40	red bed
180	406	226	brocken anhydrite and red bed
406	420	14	lime
420	423	3	water
423	470	47	lime, T.D.
			Oil pay 458-464