

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Submit in triplicate
(Other instructions on re-
verse side)

Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

LC-062619-C

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

N/A

7. UNIT AGREEMENT NAME

N/A

8. FARM OR LEASE NAME

Hitchcock "B" Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Dog Canyon Grayburg

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 28, T.16S, R.27E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different formation.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐
2. NAME OF OPERATOR Hanson Operating Company, Inc.
3. ADDRESS OF OPERATOR P. O. Box 1515, Roswell, New Mexico 88202-1515 ARTESIA, OFFICE
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
Unit P, SE $\frac{1}{4}$ SE $\frac{1}{4}$, 660' ~~FEL~~ & 660' FEL, Sec. 28, T.16S, R.27E
14. PERMIT NO. 30-015-23047
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3438' GR

MAR 14 '90

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐ PULL OR ALTER CASING ☐
FRACTURE TREAT ☐ MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐ ABANDON* ☒
REPAIR WELL ☐ CHANGE PLANS ☐
(Other) ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐ REPAIRING WELL ☐
FRACTURE TREATMENT ☐ ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐ ABANDONMENT* ☐
(Other) ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

It is proposed to Plug & Abandon this well in the following manner:

- 1) Set a CIBP @ 1330' to isolate perforations at 1353-1389' & 1402-1408', circulate the casing w/9# mud laden fluid. Set a 35' 4sx Class "C" cement plug on top of CIBP.
- 2) Set a 100' ^{35'} 12 sx Class "C" cement plug 50' into the base of the 8-5/8" casing, set @ 903'. TAG PLUG.
- 3) Set a 50' 6 sx Class "C" plug at surface.
- 4) Install dry hole marker, clean & restore location.

All plugs will be placed w/9# mud laden fluid.

The Bureau of Land Management will be notified 24 hours in advance of operations.

A temporary working pit will be dug.

TOP 50' OF ALL ANMULI will be cemented.

18. I hereby certify that the foregoing is true and correct

SIGNED

Brenda R. Godfrey

TITLE

Production Analyst

DATE

02/13/90

(This space for Federal or State office use)

Orig. Signed by Adam Salameh

APPROVED BY

TITLE

PETROLEUM ENGINEER

DATE

3-7-90

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side