

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

NMOCC COPY

SUBMIT IN TRIPLI
(Other instructions on re-
verse side)

Copy to SF
Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR **ILLECIBLE**

3. ADDRESS OF OPERATOR **Libbock, Texas**

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5. LEASE DESIGNATION AND SERIAL NO.
025603

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Gravia

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT
Gravia Yates 7-24-78

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 12 T.17S R.27E

12. COUNTY OR PARISH

13. STATE

RECEIVED

NOV 3 1977

O.C.C.

16. Check Appropriate Box To Indicate Nature of Work or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

PULL OR ALTER CASING ☐

FRACTURE TREAT ☐

MULTIPLE COMPLETE ☐

SHOOT OR ACIDIZE ☐

ABANDON* ☐

REPAIR WELL ☐

CHANGE PLANS ☐

(Other) ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

REPAIRING WELL ☐

FRACTURE TREATMENT ☐

ALTERING CASING ☐

SHOOTING OR ACIDIZING ☐

ABANDONMENT* ☐

(Other) ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Notify operator 24-hrs.
2. Open 7" cap. on new 1" loose (note 7)
3. Run to 115'
4. Run 24-hrs. out.
5. Run plug 115' rise 1 in. 50' inside 7" cap. (set to 420')
6. Load hole with heavy mud
7. If 7" cap. loose pull (note 1) (16-protect out. plug)
8. If pull 7" cap. inside from water zone (115-50') 24-hrs. out & tag.
9. If cap pull 7" cap. pump to surface & load over 7" cap. to well bore.
10. If pull 7" cap. circ. 10-24-hrs. out. surface & load over 7" cap. to well bore.

RECEIVED

NOV 2 1977

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED **Lee J. Lara**

TITLE **Engineer**

DATE **November 1, 1977**

(This space for Federal or State office use)

APPROVED BY **Lee J. Lara**
CONDITIONS OF APPROVAL, IF ANY:

TITLE **ACTING DISTRICT ENGINEER**

DATE **NOV 2 - 1977**

Subject to rapping well pad & access road not used

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of putting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO 680-379

RECEIVED

NOV 3 1977

U.S. DEPT. OF THE INTERIOR