

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Las Cruces  
Lease No. 062620  
Unit Diamond Mound

## SUNDRY NOTICES AND REPORTS ON WELLS

|   |   |
|---|---|
| NOTICE OF INTENTION TO DRILL.....                   | SUBSEQUENT REPORT OF WATER SHUT-OFF.....        |
| NOTICE OF INTENTION TO CHANGE PLANS.....            | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING..... |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....     | SUBSEQUENT REPORT OF ALTERING CASING.....       |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL..... | SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....  |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....        | SUBSEQUENT REPORT OF ABANDONMENT.....           |
| NOTICE OF INTENTION TO PULL OR ALTER CASING.....    | SUPPLEMENTARY WELL HISTORY.....                 |
| NOTICE OF INTENTION TO ABANDON WELL.....            |   |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

W. P. Thurmon No. 1

Hobbs, New Mexico July 13, 19 51

Well No. 1 is located 660 ft. from [N] line and 660 ft. from [E] line of sec. 11

NE 1/4 Sec. 11

(1/4 Sec. and Sec. No.)

Wildcat

(Field)

16-S

(Twp.)

27-3

(Range)

N.E.P.M.

(Meridian)

New Mexico

Eddy

(County or Subdivision)

The elevation of the derrick floor above sea level is 3669 ft.

**ILLEGIBLE**

### DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

In accordance with Mr. E. L. Shafer's telephone conversation with Mr. Knauf of the U. S. Geological Survey Artesia office and our Notice of Intention to Abandon Well, the following 100' cement plugs were placed in the hole:

10,770' - 10,670' w/40 sacks

6,790' - 6,690' w/40 sacks

10,330 - 10,230' w/40 sacks

1,680 - 1,580 w/40 sacks

9,580 - 9,480 w/40 sacks

Balance of hole filled with 12# mud.

A casing pulling unit was moved in on 7-6-51 and the 9 5/8" casing was shot off and pulled from a depth of 497'. A 100' cement plug was set from 550' to 490' with 40 sacks and a 50' plug set from 50' to surface with 40 sacks, with intervals between cement plugs filled with 12# mud.

A 4" pipe marker was erected and the location was restored to original condition.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Continental Oil Company

Address Box CC

Hobbs, New Mexico

By [Signature]

Title District Superintendent