

UNITED STATES
DEPARTMENT OF THE INTERIOR
NMOC COPY GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions to
see inside)Form approved
Budget Bureau No. 42 H1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER		RECEIVED	
2. NAME OF OPERATOR Cities Service Company		OCT 27 1978	
3. ADDRESS OF OPERATOR P.O. Box 1919, Midland, TX 79702		O. C. C. ARTESIA OFFICE	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1650' from South line, 2310' from West line of Section 35, T-17S, R-27E, Eddy County, New Mexico		8. FARM OR LEASE NAME Magruder C	
14. PERMIT NO.		9. WELL NO. 15	
15. ELEVATIONS (Show whether of, at, on, etc.) 3634' GR		10. FIELD AND POOL, OR WILDCAT Undesignated Morrow	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 35, T-17S, R-27E	
		12. COUNTY OR PARISH Eddy	
		13. STATE New Mexico	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETION

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

T.D. 9900'. Shale.

Ran 56 joints (1842.65') of 4-1/2" 11.6#, 8R, N80, LT&C, 93-1/2 joints (3828.72') of 4-1/2" 11.6# 8R, K55, LT&C and 106 joints (4212.93') of 4-1/2" 10.5# 8R, K55, ST&C Casing set at 9900' and cemented with 600 sacks Class H W/O.6% CFR-2 & 5# KCL/sack. Plug down at 1115 MDT 5-29-78. Bumped float 1500# - ok. WOC 24 hrs. Ran temp. survey. Top of cement at 8310'.

RECEIVED
JUN 5 1978
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Region Operations Manager

DATE

5-31-78

(This space for Federal or State office use)

APPROVED BY

TITLE ACTING DISTRICT ENGINEER

DATE

OCT 26 1978

CONDITIONS OF APPROVAL, IF ANY: