Form 9-331 (May 1963)

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

U. ED STATES SUBMIT IN TRI CATE OF THE INTERIOR Verse side)

'ATE

SHOOTING OR ACIDIZING

5. LEASE DESIGNATION AND SERIAL NO.

	57798
--	-------

GEOLOGICAL	SURVEI

SUNDRY NOTICES AND REPORTS ON WELLS

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

ABANDONMENT

	(Do not use this form for proposals Use "APPLICATION"	to drill or to deepen or plug back to a different reservoir. N FOR PERMIT—" for such proposals.)	
1.	OIL GAS X OTHER	RECEIVED	7. UNIT AGREEMENT NAME
2.	Cities Service Compar	ny ✓ JAN 2 1979	8. FARM OR LEASE NAME. Magruder C
3.	Box 1919, Midland, To		9. WELL NO. # 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
4.	At surface	e, 2310' from West line of Sec 35,	Undesignated Transition 11. SEC., T., R., M., OR BLK. AND
	T-17S, R-27E, Eddy Co	Sec 35, T-175, R-27E	
14.	PERMIT NO.	5. ELEVATIONS (Show whether DF, RT, GR, etc.) 3634 GR	12. COUNTY OR PARISH 13. STATE Eddy 12. New Mexico
16.	Check Appro	priate Box To Indicate Nature of Notice, Report, o	or Other Data 1990
		OR ALTER CASING WATER SHUT-OFF FRACTURE TREATMENT	REPAIRING WELL ALTERING CASING

(Note: Report results of multiple completion on Well-Completion or Recompletion Report and Log form.) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones per

T.D. 9900' PBTD 9465', Morrow 9555-9738', Strawn 8107-8257' found to be uneconomical. We propose to plug this well as follows:

- POOH w/2-3/8" tbg MIRU. Kill Strawn w/2% KCL wtr. ND tree. NU BOP. & Baker Lok-Set pkr.
- Set 4-1/2" CIBP on wireline @ approx. 8050'. Dump 3 sx cmt on CIBP w/dump bailer. New PBTD should be 8015'.
- Shoot off 4-1/2" csg @ approx. 7500' & lay down csg.
- RIH w/2-3/8" tbg open ended, circ. hole w/mud laden fluid, & spot following cmt plugs:
 - 150' cmt plug 1/2 in & 1/2 out of 4-1/2" csg stub?
 - 150' emt plug at 5300' to P&A Abo.
 - 100' cmt plug at 2200'.

ABANDON*

CHANCE PLANS

100' cmt plug 1/2 in & 1/2 out of 9-5/8" shoe @

10 sx cmt cap in top of 9-5/8" csg.

HOLE SIZE CHANGES FROM 8-3/4" to 7-7/8" @ 5726'.

- 5. Install 4" dry hole marker.
- RD & MO pulling unit.

RECEIVE NOV 20 1918

S. I hereby certify that the foregoing is true and correct SIGNED	Region Operations Mgr.	рать = 11/16/78.
(This space for Federal or State office use) APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	TITLE ACTING DISTRICT ENGINEER	DATE DEC 28 1978