

957
92

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
2040 Pacheco St.
Santa Fe, NM 87505

WFL API NO.

30-015-00650

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

E-379

7. Lease Name or Unit Agreement Name

State "A"

8. Well No.

2

9. Pool name or Wildcat

Empire Yates 7 Rivers

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

2. Name of Operator

Pronghorn Mgt. Corp.

3. Address of Operator

P.O. Box 1772 Hobbs, N.M. 88240

4. Well Location

Unit Letter B : 330 Feet From The North Line and 1650 Feet From The East Line

Section

36

Township

17 S

Range

27 E

NMPN:

Eddy

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3616 GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☒

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Move in and rig up p+a equipment.
2. Tag for total depth → Perf. CS9 squeeze 100' of cmt outside of CS9 380' to 480' leave 100' of cmt inside CS9
3. Cement well from total depth 380' to 480' TAG to surface. → Perf CS9. squeeze 60' of cmt outside CS9 10' to 70' - Leave 60' of cmt inside of CS9 10' to 70'
4. Erect day hole in area.
5. Clean location.

Notify OCD 24 hrs. prior to any work done

Salt gel mud consisting of 10#
Brine W/25# of gel per bbl
must be placed between each plug

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE

DATE

TYPE OR PRINT NAME

TELEPHONE NO.

(This space for State Use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED
OCD - ARTESIA
SEP 17 2001

Operator Bronghorn Mgt Corp-
Well State A #2
Unit B Section 36 Township 17 Range 27
API # 30 -- 015 -- 00650

- TOPS

Water 220-345

Oil Zone 320-521

- Salt gel mud consisting of 10# brine with 25# of gel per barrel must be placed between each plug
- Install Dry Hole Marker

Notify OCD 24 hrs. prior to any work done

← Section Plug - Perf casing square
30' of cement
10' - 30'
Leave 30' of cement
5' - 7'

← Perf casing - square 100' of cement 330-543 TA9
Leave 100' of cement
64 cement @ 50%

Toc
422'

5"
485'
205'
8' bit