

Submit 3 Copies  
To Appropriate  
District Office  
**DISTRICT I**  
1625 N. French Dr., Hobbs, NM 88240

**DISTRICT II**  
811 South First, Artesia NM 88210

**DISTRICT III**  
1000 Rio Brazos Rd., Aztec, NM 87410

State of New Mexico  
En/ Minerals and Natural Resources Department

## OIL CONSERVATION DIVISION

2040 South Pacheco  
Santa Fe, NM 87505

Form C-103  
Revised March 25, 1999

WELL API NO. 30-015-00674
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. 1579
7. Lease Name or Unit Agreement Name: Ramapo
8. Well No. # 2
9. Pool name or Wildcat Empire-Yates-Seven Rivers
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3620' DF

### SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>	2. Name of Operator Gas Well Services, Inc.
3. Address of Operator 26 E. Compress Rd. Artesia, NM. 88210	4. Well Location Unit letter K : 2310' feet from the West line and 2310' feet from the South line Section 36 Township 17S Range 27E NMPM Eddy County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3620' DF	

Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

#### NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☒ MULTIPLE COMPLETION ☐

OTHER: ☐

#### SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. Plug back to depth of 480'.
2. Run 4½" liner to depth of appx. 480'.
3. Circulate cement.
4. Clean out to original depth of 515'.
5. Run tubing and rods.
6. Return well to production.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jack Matthews TITLE President DATE July 1, 1999.

Type or print name Jack Matthews

Telephone No. 746-2675

(This space for State use)

APPROVED BY Jim W. Green TITLE District Supervisor DATE 7-1-99

Conditions of approval, if any: