


N.

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## WELL RECORD



Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES  
LOCATE WELL CORRECTLY

DUPLICATE

F.G. Keyes

State

Company or Operator

Lease

Well No. 2 in C SENE of Sec. 9 T. 17

R. 28, N. M. P. M., Artesia Field, Eddy County.

Well is 1980 feet south of the North line and 660 feet west of the East line of Sec. 9

If State land the oil and gas lease is No. B-2179 Assignment No. Original

If patented land the owner is Address

If Government land the permittee is Address

The Lessee is F.G. Keyes Address Roswell Box 936

Drilling commenced June 6 1938 19 Drilling was completed Sept. 8 1938 19

Name of drilling contractor F.G. Keyes Address

Elevation above sea level at top of casing 3521 feet.

The information given is to be kept confidential until 19

## OIL SANDS OR ZONES

No. 1, from 1358 to 1363 GAS No. 4, from to

No. 2, from 1407 to 1421 OIL No. 5, from to

No. 3, from 1713 to 1724 OIL No. 6, from to

## IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 228 to 235 salty feet.

No. 2, from 1130 to 1145 salty feet.

No. 2, from to feet.

No. 4, from to feet.

## CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
12 1/2				65				
10				140				
8 1/2				434				
6 1/2				1223				

## MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
8"	8 1/2"	1223	25	Halliburton		40 sacks

## PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

## RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		Nitro	40 qts	Sept. 9		

Results of shooting or chemical treatment

## RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

## TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet

Cable tools were used from top feet to bottom feet, and from feet to feet

## PRODUCTION

Put to producing Sept. 10 1938 19

The production of the first 24 hours was 66 barrels of fluid of which 100 % was oil; no % emulsion; no % water; and no % sediment. Gravity, Be. 36

If gas well, cu. ft. per 24 hours 1,000,000 Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in. 340

## EMPLOYEES

Frank Tigner, Driller

Conrad Keyes, Driller

## FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 27th

Roswell New Mex Sept. 27 1938

day of Sept. 1938 19

Name F. G. Keyes

Position Owner

Representing

Company or Operator

My Commission expires July 18, 1941

Address Roswell N.M. Box 936

## FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
15		15	soil
15	228	213	red beds lime shls
228	618	390	anhy red shl
618	759	141	lime
759	766	7	lime blu shl
766	790	24	anhy blu shl
790	821	31	lime
821	867	46	anhy blu bro shl
867	950	83	lime bro shl
950	962	12	anhy bro shl
962	999	37	lime anhy
999	1109	110	lime bro shl
1109	1130	21	brown shl
1130	1145	15	red sand salt water
1145	1358	213	lime
1358	1363	5	gas sand
1363	1407	44	lime
1407	1421	14	oil sand
1421	1454	33	lime bro shl
1454	1577	223	lime anhy bro shl
1577	1610	33	lime hard
1610	1625	15	lime brown sdy
1625	1631	6	lime grey
1631	1650	29	lime bro shl
1650	1706	56	lime grey hard
1706	1713	7	lime blue
1713	1724	11	oil sand
1734 TD			