

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office _____

Lease No. 0181Unit K.

RECEIVED

AUG 2 4 1961

D. D. C.
ARTESIA, OFFICE

APPROVED

AUG 11 1961

A. R. BROWN
ACTING DISTRICT ENGINEER

VARIETY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

August 2, 69

Well No. 1 is located 650 ft. from XXN line and 2310 ft. from XXE line of sec. 10NE-34 10 17 28 NMPN
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)Red Lake Eddy New Mexico
(Field) (County or Subdivision) (State or Territory)The elevation of the derrick floor above sea level is 3545 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

I propose to drill 10" hole & set 24" 8 5/8" used casing at approximately 350', and mud same to shut off surface water. Drill 8" hole to 2000' to test the Grayburg and Premier sections. If well will warrant completion, will set bridge below 8 5/8" surface casing and cement with 50 sacks. Will run 3 1/2" or 4 1/2" casing for production string and cement with 100 sacks cement & complete well.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Tom BoydAddress 102 S. 2nd St.Artesia, New MexicoBy Tom BoydTitle Owner