(Form	C-162)
(Revised	7/1/52)

NUMBER OF COPIES RECEIVED				
DI	TRIBUTI	N		
SANTA FE			1	
FILE				
U.S.G.S.		1		<u>f</u> '
LAND OFFICE				
	OIL	1		_
TRANSPORTER	GAS			
PROBATION OFFIC	εε			
OPERATOR				_

EW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

strict Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate	Nature	of	Notice by	Checking	Below
----------	--------	----	-----------	----------	-------

Notice of Intention to Change Plans		Notice of Intention to Temporarily Abandon Well				Notice of Intention to Drill Deeper	
NOTICE OF INTENTION TO PLUG WELL	x	Notice of Intention to Plug Back				Notice of Intention to Set Liner	
Notice of Intention to Squeeze		Notice of Intention to Acidize				Notice of Intention to Shoot (Nitro)	
Notice of Intention to Gun Perforate					Notice of Intention (Other)		
OIL CONSERVATION COM SANTA FE, NEW MEXICO	MISSION		(P	lace)	Ma	urch 23, 1963	
Gentlemen:							
Following is a Notice of Ir	atention to d	o certain work	as describe	d below at	the		••••••
Charles B. Read		S	uperior	State			D.L
NW 1/2 NW 1/4 of (40-acre Subdivision)	Sec. 12	, т <mark>1</mark> '	75, r	28E	,NMPM.,	.Well No1 in East Red Lake	(Unit) Pool
Eddy	Co	unty.					
	FUI	L DETAILS	OF PRO	POSED	PLAN OF	WORK	

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Propose to Flug and Abandon on March 24, 1963, by circulating oil off hole, spot 25 sx. cement from 1432' to 1674' T. D., shoot casing with nitroglycerine at approximately 1035' and spot 25 sk. 100' plug at cut off. Spot 25 sk. plug at base of surface casing from 205' to 295' and 10 sk. plug at surface. Heavy mud will be spotted between all plugs. Each plug will be tested for shut off at 1000# for 30 minutes. Casing will be pulled from cut off point, dry hole marker installed, cellar filled, and location cleaned and restored. 255' of 8-5/8'' surface casing will be left in hole.

		RET	
8961 9	I Aqu		
Approved Except as follows:	•		Charles B. Read
	4		By Coharlos Bollea
Approved OIL CONSERVATION	COMMISSIO	N	Position
•	stron	/	NameCharles B. Read
Title	V9 888 130/	/	Address