

Submit 3 copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

C157  
Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240  
DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210  
DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504 -2088

WELL API NO.  
0-015-01373  
5. Indicate Type of Lease  
STATE ☒ FEE ☐  
6. State Oil & Gas Lease No.  
B-8617  
7. Lease Name or Unit Agreement Name  
Spurck F State  
8. Well No.  
3  
9. Pool name or Wildcat  
Red Lake, QN, GRB

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
OIL Well ☐ GAS Well ☒ OTHER  
2. Name of Operator  
Yates Drilling Company  
3. Address of Operator  
105 South 4<sup>th</sup> St., Artesia, NM 88210

4. Well Location  
Unit Letter E 2310 Feet From The North Line 990 Feet From The West Line  
Section 15 Township 17S Range 28E NMPM Eddy County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data  
NOTICE OF INTENTION TO:  
PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐  
SUBSEQUENT REPORT OF:  
REMEDIAL WORK ☐ ALTERING CASING  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒  
CASING TEST AND CEMENT JOB  
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.  
2/19/2002 RUPU. Pulled rods and tubing. Set CIBP at 1862'. Circulated hole with 10 ppg mud and spotted 10 sxs. cement on top of CIBP. TOC 1762'. Set CIBP at 1364' and spotted 10 sxs. cement on top of CIBP. TOC 1284'. Gerry Guy, NMOCD witnessed procedure.  
2/20/2002 Cut casing at 580', could not pull casing free., could not circulate well. RIH to 630' and spotted 25 sxs 2% CCL. Spotted cement, WOC. Tagged plug at 395'. Spotted plug 100' to surface with 10 sxs. of cement.  
Cut off wellhead, cleaned location and installed dry hole marker.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.  
SIGNATURE Karen J. Leishman TITLE Engineering Technician DATE 3/7/2002  
TYPE OR PRINT NAME Karen J. Leishman TELEPHONE NO. 505-746-0308

(This space for State Use)  
APPROVED BY [Signature] TITLE Compliance Officer DATE 3-25-02  
CONDITIONS OF APPROVAL, IF ANY: