


APPROVED



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office .....

Lease No. NM-080268

Unit .....

RECEIVED

AUG 3 1962

D. C. C.  
ARTESIA, OFFICE

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Copy February 15, 1961

Original May 18, 1960

19.....

Federal

Well No. 2 is located 990 ft. from ~~XX~~ [S] line and 2310 ft. from [E] line of sec. 15SWSE Sec. 15  
(1/4 Sec. and Sec. 15)175  
(Twp.)28E  
(Range)N. M. P. M.  
(Meridian)Red Lake  
(Field)Sady  
(County or subdivision)New Mexico  
(State or Territory)

The elevation of the derrick floor above sea level is 3572 ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

FEB 15 1961

U. S. G. C. SURVEY  
ARTESIA, NEW MEXICO

Pursuant to oral permission granted by telephone conversation on approximately May 8, 1960, we plugged this well as follows:

We drilled to a total depth of 2192 feet and did not encounter any oil or gas in appreciable quantities. We ran 153 feet of 10 3/4" casing and 419 feet of 8 5/8" casing, landing both to shut off water encountered at 80-85 feet and 350-55 feet respectively. All casing was recovered.

We plugged the well as follows: 50 feet of cement in bottom; filled with mud to 1600 feet; cement plug 1600-1550; filled with mud to 1200 feet; 50 ~~XXXXX~~ feet of cement 1200-1150; filled with mud to 400 feet; 50 feet of cement 400-350 feet; filled with mud to surface; cemented cellar with 10 sacks of cement; put up marker and cleaned up location.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Kincaid &amp; Watson Drilling Company

Address Box 498

Artesia, New Mexico

By

Title Agent