

Submit 3 copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504 -2088

WELL API NO.

30-015-01385

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

B-8617

7. Lease Name or Unit Agreement Name

Spurck F State

8. Well No.

4

9. Pool name or Wildcat

Red Lake, Qn, Grb

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"

(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL

GAS

Well ☒

Well ☐

OTHER

2. Name of Operator

Yates Drilling Company

3. Address of Operator

105 South 4th Street, Artesia, NM 88210

4. Well Location

Unit Letter C : 990 Feet From The North Line 2310 Feet From The West Line

Section 15

Township 17S

Range 28E

NMPM

Eddy

County

3536 GW

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☒

☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

☐

PULL OR ALTER CASING ☐

OTHER: ☐

☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK

☐ ALTERING CASING

COMMENCE DRILLING OPNS.

☐ PLUG AND ABANDONMENT

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

See attachment



A Notice N.M.C.O. to witness Drilling Operations

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Karen J. Leishman

TITLE Engineering Technician

DATE

2-12-01

TYPE OR PRINT NAME Karen J. Leishman

TELEPHONE NO. 505-746-0308

(This space for State Use)

APPROVED BY

Mike Stillfield

TITLE Field Rep. II

DATE

2/27/01

CONDITIONS OF APPROVAL, IF ANY:

30-015-01385

C-15-175-28e

Yates Drilling Co.

Spurlock Fr. #4

Tops

T. Y. - 466'

T. Q. - 1245'

T. SA. - 2007'

10" csg

133'

Pulled

* 10' surface Plug.

* Spot 100' cement Plug 593' - 433' 714

* Cut & Pull 5 1/2" csg

8 5/2" csg

493'

* Spot 25' cement Plug 1192' - 1092'

* Circ brine gel.

* Run & set CFBP @ 1944' w/ 100' cement.

T. Perf. - 1994'

5 1/2" csg

2074'

w/ 250' cement

TOC - 1280'

**Spurck F State 004
990' FNL & 2310 FWL
C-15-17S-28E
Eddy, NM
30-015-01385**

Proposed Plug and Abandonment Procedure

- 1) Clear and level location.
- 2) Check anchors and replace as necessary.
- 3) Rig up workover unit.
- 4) Pull rods, pump and tubing out of hole.
- 5) Inspect tubing.
- 6) Pick up rental tubing if necessary.
- 7) RIH w/ CIBP and set at +/- 1944' (50' above top perforation).
- 8) Circulate hole w/10 ppg mud.
- 9) Spot 100' cement plug on top of CIBP (1844' - 1944').
- 10) Spot 100' Cement plug across top of Queen (1192' - 1292')
- 11) POH with tubing.
- 12) Cut and pull 5 1/2" casing at ~~457'~~ 543' ^{543'}
- 13) RIH w/ tubing and spot cement plug from 407' to ~~507'~~ 543'
- 14) POH w/ tubing.
- 15) WOC
- 16) RIH and tag cement.
- 17) Spot additional cement as necessary.
- 18) Spot cement plug from 0 to 183'.
- 19) Erect regulation dry hole marker.
- 20) Remove all equipment from location.