

Dec. 1973

COMMISSION

Form Approved.  
Budget Bureau No. 42-R1424

CLSF

UNITED STATES  
DEPARTMENT OF THE INTERIOR

OCT 13 '87 GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other ☒ Injection

2. NAME OF OPERATOR

Kersey &amp; Company

3. ADDRESS OF OPERATOR

P.O. Box 316, Artesia, NM 88211-0316

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE:

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON\* ☒

(other)

5. LEASE

Delhi Reid #1 LC-048479(A)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

RLPSU Flood

8. FARM OR LEASE NAME

RLPSU - Tract 2

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Red Lake-Q-G-SA

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Unif F

2310 N, 2310 W, Sec. 20-17S-28E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DE, KDB, AND WD)

3622.2

(NOTE: Report results of multiple completion on zone change on Form 9-330.)

RECEIVED

OCT 13 11 00 AM '87

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. Dump at least 200' cement 1971-1802' (TAG)
2. Estimated TOC 800 - Perforate at 750', set cement retainer at 725' and attempt to squeeze annulus to bring cement back to surface casing - but preferably surface.
3. Sting out retainer & leave 55' cement on retainer.
4. Spot 100' cement, 50' above and 50' below 8 5/8" casing shoe (TAG)
5. Leave 50' surface plug- erect marker.
6. Restore surface

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Harold Kersey TITLE Co-Owner DATE 9-24-87

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE 10-2-87

CONDITIONS OF APPROVAL, IF ANY: