<u>COPY</u>

EGF

NEW MEXICO OIL CONSERVATION COMMISSION

يا المعار

SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approval sould derfellowed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING
NOTICE OF INTENTION TO REPAIR WELL	NOTICE OF INTENTION TO PLUG WELL Notice of Plugging Results X
NOTICE OF INTENTION TO DEEPEN WELL	
Arte	sia, New Mexico November 26, 1947
	Place Date
OIL CONSERVATION COMMISSION, Santa Fe, New Mexico	
Gentlemen:	
Following is a notice of intention to do certain work as	described below at the
Paton Brothers State (Red Lake	well No. 1 in NW SE
of Sec. 21 , T. 17S R. 28E	, N. M. P. M., Red Lake Field
EddyCounty.	
	ROPOSED PLAN OF WORK
	ES AND REGULATIONS OF THE COMMISSION
8" Casing was set at 595'; 7" Casing was cemented @ 1748	With 25 sacks of coment.
8" Casing was set at 595'; 7" Casing was cemented @ 1748 Hole was filled with heavy mu a plugged back depth of 2031' 1970'; knocked off and pulle mud to 600' and pulled 8" cas and set cement plug; filled cement plug; filled to surfa regulation 4' marker in cemen	With 25 sacks of cement; d from total depth of 2075' and to 1970'; cement plug set at d 7" casing; filled with heavy ing; filled with mud to 375' with mud to 100' and set a ce with heavy mud and set a t.
7" Casing was cemented @ 1748 Hole was filled with heavy mu a plugged back depth of 2031' 1970'; knocked off and pulle mud to 600' and pulled 8" cas and set cement plug; filled cement plug; filled to surfa regulation 4' marker in cemen	With 25 sacks of cement; d from total depth of 2075' and to 1970'; cement plug set at d 7" casing; filled with heavy ding; filled with mud to 375' with mud to 100' and set a ce with heavy mud and set a t. 947 and completed November 25, 1947. by the operator. This report
8" Casing was set at 595'; 7" Casing was cemented @ 1748 Hole was filled with heavy mu a plugged back depth of 2031' 1970'; knocked off and pulle mud to 600' and pulled 8" cas and set cement plug; filled cement plug; filled to surfa regulation 4' marker in cemen Work commenced November 21, 19 Form C-103 was not submitted is submitted February 6, 1953. Approved 11-4 19-4	3' with 25 sacks of cement; id from total depth of 2075' and to 1970'; cement plug set at id 7" casing; filled with heavy ing; filled with mud to 375' with mud to 100' and set a ce with heavy mud and set a t. 947 and completed November 25, 1947. by the operator. This report
8" Casing was set at 595'; 7" Casing was cemented @ 1748 Hole was filled with heavy mu a plugged back depth of 2031' 1970'; knocked off and pulle mud to 600' and pulled 8" cas and set cement plug; filled cement plug; filled to surfa regulation 4' marker in cemen Work commenced November 21, 19 Form C-103 was not submitted is submitted February 6, 1953.	3' with 25 sacks of cement; id from total depth of 2075' and to 1970'; cement plug set at id 7" casing; filled with heavy ing; filled with mud to 375' with mud to 100' and set a ce with heavy mud and set a t. 947 and completed November 25, 1947. by the operator. This report
8" Casing was set at 595'; 7" Casing was cemented @ 1748 Hole was filled with heavy mu a plugged back depth of 2031' 1970'; knocked off and pulle mud to 600' and pulled 8" cas and set cement plug; filled cement plug; filled to surfa regulation 4' marker in cemen Work commenced November 21, 19 Form C-103 was not submitted is submitted February 6, 1953. Approved 11-4 19-4	3' with 25 sacks of cement; ad from total depth of 2075' and to 1970'; cement plug set at ad 7" casing; filled with heavy ing; filled with mud to 375' with mud to 100' and set a ce with heavy mud and set a t. 947 and completed November 25, 1947. 947 by the operator. This report 947 PATON BROTHERS 947 PATON BROTHERS 947 Partner
8" Casing was set at 595'; 7" Casing was cemented @ 1748 Hole was filled with heavy mu a plugged back depth of 2031' 1970'; knocked off and pulle mud to 600' and pulled 8" cas and set cement plug; filled cement plug; filled to surfa regulation 4' marker in cemen Work commenced November 21, 19 Form C-103 was not submitted is submitted February 6, 1953. Approved 11-4 19-4	3' with 25 sacks of cement; id from total depth of 2075' and to 1970'; cement plug set at ad 7" casing; filled with heavy ing; filled with mud to 375' with mud to 100' and set a ce with heavy mud and set a t. 947 and completed November 25, 1947. 947 by the operator. This report 47. PATON BROTHERS 47. Operator Operator By Company of Operator
8" Casing was set at 595'; 7" Casing was cemented @ 1748 Hole was filled with heavy mu a plugged back depth of 2031' 1970'; knocked off and pulle mud to 600' and pulled 8" cas and set cement plug; filled cement plug; filled to surfa regulation 4' marker in cemen Work commenced November 21, 19 Form C-103 was not submitted is submitted February 6, 1953. Approved 11-4 19-4	3' with 25 sacks of cement; id from total depth of 2075' and to 1970'; cement plug set at ad 7" casing; filled with heavy ing; filled with mud to 375' with mud to 100' and set a ce with heavy mud and set a t. 947 and completed November 25, 1947. 947 by the operator. This report 47. PATON BROTHERS Partner Position
8" Casing was set at 595'; 7" Casing was cemented @ 1748 Hole was filled with heavy mu a plugged back depth of 2031' 1970'; knocked off and pulle mud to 600' and pulled 8" cas and set cement plug; filled to surfa regulation 4' marker in cemen Work commenced November 21, 19 Form C-103 was not submitted is submitted February 6, 1953. Approved 11-4 19.4	<pre>i with 25 sacks of cement; d from total depth of 2075' and to 1970'; cement plug set at d 7" casing; filled with heavy ing; filled with mud to 375' with mud to 100' and set a ce with heavy mud and set a t.</pre> 947 and completed November 25, 1947. by the operator. This report 47. PATON BROTHERS PATON BROTHERS Partner Position Partner Partner Part O Part 667



 $\frac{1}{\sqrt{2}}$ and $\frac{1}{\sqrt{2}}$ is the second second

ч.

.

 $1 \leq 1 \leq \frac{1}{2} \leq 1 \leq \frac{1}{2} \leq 1 \leq \frac{1}{2} \leq 1 \leq \frac{1}{2} \leq \frac{1}$

an en born a born a born a born a superior a A superior provincia de la superior de la superior de la superior de la superior a superior a superior a superi A ferrar a superior a s

and the second second